

Data Sheet

Constellation[®] ES.2

2TB and 3TB Capacity-Optimized Enterprise Hard Drives for Bulk-Data Applications

Key Advantages

- Highest-capacity enterprise drive for demanding data growth¹
- Fifth-generation SAS and SATA drives designed for 24x7 reliability
- SAS-based, end-to-end data integrity and enhanced error correction for accurate data storage
- Best-in-class enhanced rotational vibration tolerance ensures consistent performance.
- Improved power and cooling efficiencies with low power consumption and enhanced PowerChoice™ technology
- Multi-drive firmware maximized for enterprise system availability
- Robust performance with dual processor and ramp load technologies
- Self-Encrypting Drive (SED) option (AES-256) cuts IT drive retirement costs while securely protecting data where it lives—on the drive.²
- FIPS 140-2 Validated™ drives protect *Sensitive but Unclassified and Protected* class data.^{2,3}

Best-Fit Applications

- High-capacity bulk-data storage
- Mainstream enterprise external storage arrays (SAN, NAS, DAS)
- Enterprise backup and restore—D2D, virtual tape
- Centralized surveillance
- Cloud storage

¹ Seagate recommends validating your configuration with your HBA/RAID controller manufacturer to ensure full 3TB capacity capabilities.

² Self-Encrypting Drives (SED) and FIPS 140-2 Validated drives are not available in all models or countries. May require TCG-compliant host or controller support.

³ See FIPS 140-2 Level 2 Certificate at <http://csrc.nist.gov/groups/STM/cmvp/documents/140-1/1401val2011.htm#1635>



Constellation[®] ES.2



2TB and 3TB Capacity-Optimized Enterprise Hard Drives for Bulk-Data Applications

Specifications	6Gb/s SAS		SATA 6Gb/s	
	3TB ^{1,2}	2TB ¹	3TB ^{1,2}	2TB ¹
Standard Model Number	ST33000650SS	ST32000645SS	ST33000650NS	ST32000645NS
SED (AES-256) Model Number	ST33000651SS ³	ST32000646SS ³	ST33000651NS ³	ST32000646NS ³
SED (AES-256) FIPS 140-2 Model Number	ST33000652SS ^{3,4}	ST32000647SS ^{3,4}	ST33000652NS ^{3,4}	ST32000647NS ^{3,4}
Features				
Protection Information	Yes	Yes	—	—
Low Halogen	Yes	Yes	Yes	Yes
Cache, Multisegmented (MB)	64	64	64	64
Reliability/Data Integrity				
Mean Time Between Failures (MTBF, hours)	1.2 million	1.2 million	1.2 million	1.2 million
Reliability Rating @ Full 24x7 Operation (AFR)	0.73%	0.73%	0.73%	0.73%
Nonrecoverable Read Errors per Bits Read	1 sector per 10E15	1 sector per 10E15	1 sector per 10E15	1 sector per 10E15
Power-On Hours per Year	8760	8760	8760	8760
Bytes per Sector	512, 520, 528	512, 520, 528	512	512
Limited Warranty (years) ⁵	3	3	3	3
Performance				
Spindle Speed (RPM)	7200	7200	7200	7200
Interface Access Speed (Gb/s)	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5
Max. Sustained Transfer Rate (MB/s)	155	155	155	155
Seek Time, Average Read/Write (ms)	8.5/9.5	8.5/9.5	8.5/9.5	8.5/9.5
Average Latency (ms)	4.16	4.16	4.16	4.16
Interface Ports	Dual	Dual	Single	Single
Rotational Vibration @ 1500 Hz (rad/sec ²)	12.5	12.5	12.5	12.5
Power Consumption				
Idle (W)	7.4	7.4	7.7	7.7
Typical Operating, Random Read (W)	11.3	11.3	10.7	10.7
Power Supply Requirements	+12V and +5V	+12V and +5V	+12V and +5V	+12V and +5V
PowerChoice™ Technology	Yes	Yes	Yes	Yes
Environmental				
Temperature, Operating (°C)	5 to 60	5 to 60	5 to 60	5 to 60
Vibration, Nonoperating: <5Hz to 500Hz (Gs)	4.9	4.9	4.9	4.9
Shock, Operating, 2ms (Read/Write) (Gs)	70/40	70/40	70/40	70/40
Shock, Nonoperating, 1ms and 2ms (Gs)	300	300	300	300
Physical				
Height (in/mm, max) ⁶	1.028/26.10	1.028/26.10	1.028/26.10	1.028/26.10
Width (in/mm, max) ⁶	4.010/101.85	4.010/101.85	4.010/101.85	4.010/101.85
Depth (in/mm, max) ⁶	5.787/147.00	5.787/147.00	5.787/147.00	5.787/147.00
Weight (lb/g)	1.543/700	1.543/700	1.543/700	1.543/700
Carton Unit Quantity	20	20	20	20
Cartons per Pallet	40	40	40	40
Cartons per Layer	8	8	8	8

1 One gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes when referring to drive capacity.
 2 Seagate recommends validating your configuration with your HBA/RAID controller manufacturer to ensure full 3TB capacity capabilities.
 3 Self-Encrypting Drives (SED) and FIPS 140-2 Validated drives are not available in all models or countries.
 4 May require TCG-compliant host or controller support.
 5 See FIPS 140-2 Level 2 Certificate at <http://csrc.nist.gov/groups/STM/cmvp/documents/140-1/1401val2011.htm#1635>
 6 Nearline products shipped on or after December 31, 2011, have a 3-year limited warranty. Nearline products shipped before December 31, 2011, have a 5-year limited warranty.
 7 These base deck dimensions conform to the Small Form Factor Standard (SFF-8201) found at www.sffcommittee.org.
 For connector-related dimensions, see SFF-8223.



www.seagate.com

AMERICAS
ASIA/PACIFIC
EUROPE, MIDDLE EAST AND AFRICA

Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000
 Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
 Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2011 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Wave logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Constellation, PowerChoice and the Think Green logo are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. The FIPS logo is a certification mark of NIST, which does not imply product endorsement by NIST, the U.S., or Canadian governments. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. Seagate reserves the right to change, without notice, product offerings or specifications. DS1725.4-1111US, November 2011