USB 3.1 Type C Dual Display Adapter HDMI & VGA

Part No.: 43179



Description

- Converts a USB 3.1 Type-C port to a HDMI and VGA port
- Requires DisplayPort Alternate Support by the USB 3.1 Port/Bus
- Compatible with Thunderbolt 3
- Supports resolutions up to UHD 4K 30Hz (HDMI) and 1920x1200p 60Hz (VGA)
- Plug and Play installation, no drivers required, Bus-powered
- Length (incl. housing): approx. 15 cm
- Colour: White
- 2 Year Warranty

The LINDY USB 3.1 Type C to 4K HDMI & VGA Adapter Converter allows you to connect two high definition screens to your Macbook, Ultrabook or Notebook with USB 3.1 DisplayPort Alternate Mode.

With support for both SST (Single Stream Transport) and MST (Multi-Stream Transport) the Converter can send the same display information to two screens (SST) or use both screens as individual displays with separate display information (MST), this is easily configured using the display settings of your computer.

Installation is simple as no drivers are required and the Type C's reversible design means that you do not have to pay attention to which way the cable is inserted into the port.

Technical details

- Input: USB 3.1 Type-C connector - Male
- Output: HDMI Female, VGA Female
- USB 3.1 Gen 1 Standard
- Requires DisplayPort Alternate mode
- Max. resolution: UHD 4K 4096x2160p 30Hz (HDMI) / 1920x1200p 60Hz (VGA)
- Supports SST and MST display modes
- Chipset: Synaptics VMM3332
- HDMI 1.4 compatible
- RGB format supported at 8/10/12 bits-per-component
- YCbCr format supported at 8/10/12 bits-per-component in 4:4:4/4:2:2/4:2:0 pixel format
- Audio output formats: 8-ch LPCM, compressed audio and HBR
- 24-bit audio sample size, up to 192 kHz sample rate
- Supports HDCP 1.4 content protection
- Powered via USB port, no external PSU port

© LINDY 2017