DATASHEET

Delock USB Type-C™ 3.2 Gen 2 to SATA Converter

Description

This converter by Delock can be connected via USB Type-A interface to a PC or laptop. Thus a **2.5" or 3.5" SATA HDD or SSD** with a 22 pin SATA interface can be used.



Specification

- Connectors:
  1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female
  1 x SATA 6 Gb/s 22 pin receptacle
  1 x DC jack
- Chipset: VIA VL716
- For 2.5″ and 3.5″ SATA HDD / SSD
- Supports SATA 1.5 Gb/s, SATA 3 Gb/s and SATA 6 Gb/s
- Data transfer rate up to 6 Gb/s
- LED indicator
- Colour: black
- Dimensions (LxWxH): ca. 72 x 29 x 14 mm

Power supply specification

- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.8 A
- Output: 12 V / 2 A
- Ground outside, plus inside
- Dimensions:
  inside: ø ca. 2.5 mm
  outside: ø ca. 5.5 mm
  length: ca. 10 mm

System requirements

- Chrome OS 76.0 or above
- Linux Kernel 3.12 or above
- Mac OS 10.15.1 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- Converter
- Cable USB-C™ male to USB Type-A male, length ca. 1 m
- Power supply
- User manual

Item no. 64104

EAN: 4043619641048

Country of origin: China

Package: • Retail Box

Images







General	
Suitable for data medium:	2.5″
	3.5″
Supported operating system:	Chrome OS 76.0 or above
	Linux Kernel 3.12 or above
	Mac OS 10.15.1 or above
	Windows 10 32-bit
	Windows 10 64-bit
	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
Interface	
Connector 1:	1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female
Connector 2:	1 x SATA 6 Gb/s 22 pin receptacle
connector 3:	1 x DC jack
Technical characteristics	
Chipset:	VIA VL716
Data transfer rate:	6 Gb/s
Physical characteristics	
Cable length:	1 m