


41088962



**SCHUKO socket outlet with overvoltage protection with labelling field, Screw terminals, Berker S.1/B.3/B.7, red glossy**

Technical features

**Architecture**

| | |
|---|---|
| Design | according to DIN 49440 |

**Controls and indicators**

- with acoustic fault signal

**Main electrical features**

| | |
|---|---|
| Nominal voltage | 250 V |
| Rated current | 16 A |
| Rated voltage | 250 V AC |

**Voltage**

| | |
|---|---|
| Overvoltage protection | according to EN 61643 and VDE 0675-6-11 |

**Cover, door**

- Central cover plate

**Materials**

| | |
|---|---|
| RAL colour | RAL 3003 - Ruby red |
| Design lines special colours | red |
| Colour | red |
| Colour | red |
| Material | thermoplastic |
| Surface appearance | glossy |

**Dimensions**

| | |
|---|---|
| Insertion depth | 32 mm |

**Installation, mounting**

- with spreader claws

**Connection**

| | |
|---|---|
| Connection terminals | according to IEC 60884-1 |
| Connection terminals | according to VDE 0620-1 |

- with screw terminals

**Equipment**

- with indicator LED for On/Error

**Use**

- with labelling field
- Screw terminals

### Safety

| | |
|---|---|
| Protection index IP | IP20 |
| IK protection code against mecanical impacts | 05 |
| - without enhanced contact protection | |

### Identification

| | |
|---|---|
| Main design line | Berker S.1/B.3/B.7 |
| Secondary design line(s) | Berker B.7, Berker B.3, Berker S.1 |

### Instructions

- Labelling field height arranged for P-touch strips 6 mm.