

50763552

IP55

Push-button, change-over contact surface-mounted with labelling field - illuminated, Berker W.1, polar white matt

Technical features

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

Electric current

Momentary-contact current	10 A

Materials

RAL colour	RAL 9010 - Pure white
Colour of design line	polar white
Colour	white
Colour	polarwhite
Material	thermoplastic
Surface appearance	matt

Dimensions

Height	76 mm
Width	62 mm
Labelling field (W x H)	50 x 16 mm

Installation, mounting

- for screw fastening

Connection

- with Wago clip-in 2-wire connection terminal for wiring
- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with N-terminal
- with plug-in terminals

Cable

- with one entry for 2 cables and one entry for cable and tube

Equipment

- with {\b blue} 230 V LED unit
- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Use

- with labelling field - illuminated

Safety

Protection index IP	IP55

Use conditions

Operating temperature	-40 … 30 °C
Storage/transport temperature	-50 … 50 °C

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

- Labelling field height arranged for P-touch strips 12 mm.
- Labelling fields with imprinted symbol for light, bell and door opener enclosed
- Pins of quick-release lock made of ZAMAK
- For labelling with name, information notice, etc.