



Delock Cable USB TTL male > 2.5 mm 3 pin stereo jack male 1.8 m (3.3 V)

Description

This USB TTL converter by Delock is due to its wide temperature range most suitable for industrial applications. It can be used for e.g. level converter, GPS-modules, interface controller, micro controller etc.



Specification

- Connector: USB 2.0 type A male Serial-TTL male > 2.5 mm 3 pin stereo jack male
- Pin assignment:
 1. GND
 2. TXD
 3. RXD
- Chipset: FTDI 232RL
- Cable gauge: 26 AWG
- Temperature range: -20°C to +80°C
- No-load current: 70 uA
- Converter: 5 V / 15 mA (VCC, GND)
- Compatible to UHCI / OHCI / EHCI controller
- LVTTTL 3.3 V (data) / 4 mA or HighLevel 12 mA
- Data rate 300 baud - 3 Megabaud
- Databit: 7 or 8
- Stopbits: 1 or 2
- Parity: none, space, even, odd, mark
- Flow control: software XON/XOFF or hardware RTS / CTS
- FIFO: 128 Byte – RX
256 Byte – TX
- Cable length: ca. 1.80 m

System requirements

- Windows CE 4.2, 5.0, 6.0/Windows Mobile 2003/ XP/XP-64/Vista/Vista-64/7/7-64, Mac OS 10.5 and 10.6, Linux Kernel 2.6
- PC or laptop with a free USB type A port

Package content

- USB TTL cable
- Driver CD
- User manual

Item No. 83789

EAN: 4043619837892

Country of origin: China

Package: Retail Box



Images

