

DATASHEET

19" Network Cabinet PEL 24HE 600x600 RAL7035 front glass 1-pc. rear steel 1-pc



General data

19" Network cabinet according to DIN41494

Steel sheet housing with screwed frame, completely pre-assembled, self-ventilated, dismountable

Inside front and rear 4 x 19" profiles (2 front, 2 rear-sided), galvanised, depth-adjustable in steps of 20 mm

Uprising numbering of rack units at the 19" profiles

Front door 1-part, with window of certified safety glass (thickness 5 mm)

Front door with 1-point turning handle, lockable

Rear door 1-part, steel sheet, with 1 x latch locking (lock equal to front door)

Door stop for front and rear door possible left- or right-sided, door opening angle > 180°

Detachable side walls with 2 x quick release and 1 x latch locking (lock equal to door lock)

Cabinets stackable side-by-side with and without removal of side walls, baying set Art.-No. PEL-ANR01

Roof and bottom with 2 pre-punched openings for cable entry (386 x 69 mm)

This datasheet was created automatically on 11-09-2025 . Technical changes reserved.

DATASHEET

19"Network Cabinet PEL 24HE 600x600 RAL7035 front glass 1-pc. rear steel 1-pc

Roof and bottom prepared for accommodation of 4-fan unit Art.-No. PEL-LFD04ET.GR

Cable entries and fan openings covered with screwed covers

Internal earthing of all cabinet sections

Max. load 800 kg for static equally distributed load

Protection degree IP20

Paint finish RAL7035, light grey

Included accessories: 4 x leveling feet, set of captive nuts (PU 40 pcs. for 42U, 20 pcs. for 24U), keys

Technical properties

Cabinet Series	
Degree of protection	
Demountable	
Material	
Model	
Modular spacing	
Mounting level	
Surface finishing	
Type of back door	
Type of front door	
Type of profile rail	
Type of ventilation	
With backside door	
With earthing	
With front door	
With roof plate	
With sidewall	
With socket	

Available variants

ArtNr.	Bezeichnung	Color	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Rear door locking system	Width	Height	RAL-number	Number of doors
PEL-2466GR.G1SV	19"Network Cabinet PEL 24HE 600x600 RAL7035 front glass 1-pc. rear steel 1-pc	grey	600 mm	Ein-Punkt	Glas	Stahl	800 kg	24 HE	Ein-Punkt	600 mm	1200 mm	7035	2

This datasheet was created automatically on 11-09-2025 . Technical changes reserved.



DATASHEET

19"Network Cabinet PEL 24HE 600x600 RAL7035 front glass 1-pc. rear steel 1-pc

PEL-4266GR.G1SV	19"Network Cabinet PEL 42HE 600x600 RAL7035 front glass 1-pc. rear steel 1-pc	grey	600 mm	Ein-Punkt	Glas	Stahl	800 kg	42 U	Ein-Punkt	600 mm	2000 mm	7035	2
PEL-4288GR.G1SV	19"Network Cabinet PEL 42HE 800x800 RAL7035 front glass 1-pc. rear steel 1-pc	grey	800 mm	Ein-Punkt	Glas	Stahl	800 kg	42 U	Ein-Punkt	800 mm	2000 mm	7035	2
PEL-4280GR.G1SV	19"Network Cabinet PEL 42HE 800x1000 RAL7035 front glass 1-pc. rear steel 1-pc	grey	1000 mm	Ein-Punkt	Glas	Stahl	800 kg	42 U	Ein-Punkt	800 mm	2000 mm	7035	2
PEL-2466TS.G1SV		Unique											

This datasheet was created automatically on 11-09-2025 . Technical changes reserved.

