



Overview

Model Name	APC Smart-UPS SRT Li-Ion 1500VA RM 230V
Includes	CD with software , Comms cable , Documentation CD , Installation guide , Removable support feet , USB cable , Warranty card
Standard Lead Time	Usually in Stock
Product Distribution	Australia , Austria , Belgium , Croatia , Czech Republic , Denmark , Finland , France , Germany , Greece , Hungary , Iceland , Ireland , Israel , Italy , Netherlands , New Zealand , Norway , Poland , Portugal , Russian Federation , Singapore , Slovakia (Slovak Republic) , Spain , Sweden , Switzerland

Output

Output Power Capacity	1350 Watts / 1500 VA
Max Configurable Power (Watts)	1350 Watts / 1500 VA
Nominal Output Voltage	230V
Output Voltage Distortion	Less than 2%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	220, 240V
Crest Factor	3 : 1
Crest Factor	Double Conversion Online
Waveform Type	Sine wave
Output Connections	(8) IEC 320 C13 (Battery Backup)
Bypass	Built-in Bypass

Input

Nominal Input Voltage	230V
Input Frequency	40 - 70 Hz (auto sensing)
Input Connections	IEC-320 C14
Input voltage range for main operations	50-150 (40% Load) V , 80 - 150 V
Other Input Voltages	220 , 240

Batteries & Runtime

Battery Type	Li-ion
--------------	--------

Typical recharge time	6 hour(s)
-----------------------	-----------

Communications & Management

Interface Port(s)	RJ-45 Serial , Smart-Slot , USB
Available SmartSlot™ Interface Quantity	1
Control panel	Multi-function LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes

Surge Protection and Filtering

Surge energy rating	340 Joules
---------------------	------------

Physical

Maximum Height	128.0 mm
Maximum Width	432.0 mm
Maximum Depth	590.0 mm
Rack Height	3 U
Net Weight	25.7 kg
Shipping Weight	37.4 kg
Shipping Height	445.0 mm
Shipping Width	600.0 mm
Shipping Depth	850.0 mm
Color	Black
Units per Pallet	6.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95% non-condensing %
Operating Elevation	0-3000 meters
Storage Temperature	-20 - 50 °C
Storage Relative Humidity	0 - 95% non-condensing %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	50.000 dB
Online Thermal Dissipation	450.000 BTU/hr
Protection Class	IP 20

Conformance

Approvals	CE , CE Mark , EAC , RCM , VDE
Standard warranty	5 year repair or replace