



USB 3.2 Gen 2x2 Dual M.2 NVMe SSD Enclosure with Clone Feature

No.: 43382

Easy and fast access to and cloning of M.2 NVMe SSDs

Description

- Aluminium Enclosure with USB Type C interface for two PCIe/NVMe based M.2 SSDs (not included)
- Allows access to and/or duplication of M.2 NVMe SSDs - even without connection to a host computer ["Offline Cloning"]
- USB 3.2 Gen 2x2 standard with SuperSpeed USB 20Gbps data transfer rates*
- With ultra-thin turbo fan for excellent heat dissipation, ensuring a suitable operating temperature
- 2 year warranty

The Lindy USB 3.2 Dual M.2 NVMe SSD Enclosure allows the user to install two PCIe/NVMe based M.2 SSDs as an external drive to USB hosts like laptops or PCs. The additional Clone feature enables duplicating M.2 NVMe SSDs - even without connection to a computer ["offline cloning"]. Support for the USB 3.2 Gen 2x2 standard guarantees SuperSpeed 20Gbps data transfer rates. UASP support also ensures faster speeds for UASP enabled computers.

This Lindy enclosure is compatible with PCIe/NVMe based M.2 SSDs with M key in 42, 60 and 80mm lengths. The tool-free design makes installation very easy. An included external power adapter guarantees safe power supply.

* Please note that that 20Gbps full support is only possible with a USB 3.2 2x2 host controller.

Technical details

Specifications

- Interface: USB to 2x PCIe/NVMe M.2 SSD
- Interface Standard: USB 3.2 Gen 2x2, PCIe 3.0 x2
- Supported Bandwidth: 20Gbps (USB), 32Gbps - each up to 16Gbps (PCI 3.0 x2)
- Chipset: JMS586U
- Compatibility: USB Type C equipped computers
- Special Features: supports 42/60/80mm SSDs, UASP & TRIM, LED indicator for Clone process

Connectors

- Inputs: 1 x USB Type C (Female)
- Outputs: 2 x PCIe based M.2 (Female), M key and B+M key
- Power: 5.5/2.5mm DC socket

Physical Properties

- Dimensions WxDxH: 143x77x17.5mm (5.63x3.03x0.69in)
- Cable Length: 0.25m (0.82ft)
- Housing Material: Aluminium and ABS

Net Weight: 0.174kg (0.38lb)
Operating Temperature: 5°C - 35°C (41°F - 95°F)
Storage Temperature: -10°C - 90°C (-14°F - 122°F)
Humidity: 10 - 90% RH (non-condensing)
Power Requirements: 12VDC 2A
Colour: Silver

Miscellaneous

Packaging Type: Carton Box
Packaging Dimensions: 160x100x110mm (6.30x3.94x4.33in)
Gross Weight: 0.47kg (1.04lb)
Warranty (Years): 2
Product Compliance: CE, FCC, RoHS & REACH, CP65

Package Contents

USB 3.2 Dual M.2 NVMe SSD Enclosure
0.25m USB 3.2 Gen 2x2 Type C to C cable
Multi-Country Power Supply 12VDC 2A with country adapters (EU, UK; US, AUS)
2x thermal conductive pad
2x thermal conductive plate
4x M.2 rubber retainer
Lindy Manual

Purchasing Information

No.: 43382
EAN: 4002888433822