

EUROLITE AKKU IP UP-4 QCL Spot QuickDMX MK2

Weather-proof (IP65) battery powered LED uplight with 10W 4in1 LEDs and QuickDMX

Art. No.: 41700548

GTIN: 4026397744163



List price: 474.81 €

incl. 19% VAT.

Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 5.5h depending on program used
- Integrated automatic charging of the battery and status indicator
- 4 powerful LEDs 10 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
- Frost filter
- Dimmer electronic; Dimmer speed (step response) adjustable; color blend stepless; color fade adjustable speed; color change adjustable speed; colors preset; white balance adjustable; program selection manual; pulse-width modulation; Energy-saving mode; Emergency lighting function in case of power failure
- Wash effect; strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; QuickDMX; RDM; master/slave function; wireless Master/slave function
- Flicker-free
- DMX fail mode (blackout; hold; static; full on)
- With a beam angle of 8°
- With mounting bracket; with bracket for floor use; with omega bracket
- OLED display
- Charge status indicator
- Display of the remaining battery life for the current setting
- Built with SEETRONIC connector
- Suitable for outdoor use IP65
- With pressure compensation membrane

Logistic

EAN / GTIN: 4026397744163

Weight: 4,95 kg

Length: 0.22 m

Width: 0.22 m

Height: 0.23 m

- With a KENSINGTON LOCK theft protection
- For application areas such as: Architecture; decoration; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; rental; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended
- 3 buttons on the remote control for saving your own settings

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Cable construction:	3 x 1.5 mm ² H07RN-F
Battery pack type:	1 x lithium ion 14.8 V, 6600 mAh, 97.68 Wh
Battery pack:	Battery operation up to 5.5h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED type:	4 x 10 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
Equipment:	Frost filter
DMX channels:	3; 4; 6; 8; 11
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX; QuickDMX; RDM; master/slave function; wireless Master/slave function
Projection:	Flicker-free
PWM frequency:	3000 Hz
Carrier frequency:	2.4 GHz
DMX fail mode:	Blackout; hold; static; full on
Beam angle:	8°
Beam angle (1/2 peak):	8°
Beam angle (1/10 peak):	17°
Housing color:	Black
Attachment system:	Mounting bracket Bracket for floor use Omega bracket
Display type:	OLED display
Display:	Charge status indicator , battery runtime calculation
Diameter mounting holes:	1 x Ø10mm
Use of brands:	Built with SEETRONIC connector
Material:	Aluminum
Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 17.9 cm

	Depth: 15.0 cm Height: 19.8 cm
Weight:	4.57 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x spotlight
1 x user manual
1 x power cord
1 x frost filter
1 x remote control
1 x battery
2 x knurled screw
1 x mounting bracket
2 x screw
4 x washer
1 x omega bracket