

PowerWalker VI 1500 LCD/FR

Line-Interactive UPS

1500VA Line-Interactive UPS

2x French & 2x IEC outlets, RJ11/RJ45 Surge Protection

USB Connection for monitoring

LCD display for status view

Built-in boost and buck AVR function



Item-No. 10120046



Product Features

PowerWalker VI 1500 LCD/FR is a Line- Interactive UPS which provides high performance and reliable and cost-effective backup power protection. The UPS can be automatically started up without AC power supplied. In addition, this UPS provides RJ11/RJ45 surge protection, and green power function for energy saving. Equipped with a voltage stabilizer, this UPS will continue providing clean and stable power to connected equipment and is perfect for any home or SMB (small medium business) application.


- Super smart charger to shorten charging time
- Built-in boost and buck AVR
- Simulated sine wave
- Auto restart while AC is recovering
- Off-mode charging
- Cold start function
- USB communication port
- RJ11/RJ45 surge protection
- Monitoring software included
- LCD display for status view



Backsite view



LCD Display



RJ11/RJ45 surge protection

Technical Details

Product Features

Capacity	1500VA / 900W
-----------------	---------------

Input

Voltage	220/230/240VAC
----------------	----------------

Voltage Range	160-290VAC
----------------------	------------

Output

Voltage	220/230/240VAC
----------------	----------------

Voltage Regulation	± 10 % (Battery Mode)
---------------------------	-----------------------

Frequency	50 or 60Hz
------------------	------------

Freq. Regulation	±1 Hz (Battery Mode)
-------------------------	----------------------

Waveform	Modified Sine wave
-----------------	--------------------

Transfer Time

Typical	2-6ms
----------------	-------

Battery

Type	12V / 9Ah
-------------	-----------

Quantity	2 x
-----------------	-----

Recharge Time	4h to 90%
----------------------	-----------

Full Protection

Discharge	Yes
------------------	-----

Overcharge	Yes
-------------------	-----

Overload	Yes
-----------------	-----

LCD Display

LCD Indicators	AC mode, Battery mode, Load level, Battery capacity, Input voltage, Output voltage, Overload alarm, Fault alarm and Low battery alarm.
-----------------------	--

Audio Indicators

Battery Mode	Beep every 10sec
---------------------	------------------

Low Battery	Beep every second
--------------------	-------------------

Fault	Beep every 0.5sec
--------------	-------------------

Battery Weak	Beep every 2sec
---------------------	-----------------

Battery faulty	Continuously sounding
-----------------------	-----------------------

Connections

Communication	USB
----------------------	-----

Outlets	2x French and 2x IEC
----------------	----------------------

Surge Protection	RJ11/RJ45 (in/out)
-------------------------	--------------------

Software & System Requirements

Software	ViewPower
-----------------	-----------

Operating System	For details visit: www.powerwalker.com/viewpower.html
-------------------------	--

Other	1x USB port
--------------	-------------

Product Details

Dimensions	397 x 146 x 205 mm
-------------------	--------------------

Colour	Black
---------------	-------

Weight UPS case	10.7kg
------------------------	--------

Fan Control	Auto OFF: in LINE mode ON: in battery- and AVR mode
--------------------	---

Noise Level	< 40dB
--------------------	--------

Model Code	VI 1500 LCD/FR
-------------------	----------------

Environment

Temperature	0°C – 40°C
--------------------	------------

Humidity	0 - 90% (non-condensing)
-----------------	--------------------------

Package Content

Package Content	PowerWalker VI 1500 LCD/FR, Input Power cable, IEC cable, Software CD, USB cable, manual
------------------------	--

Logistic Data

Giftbox Language	EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HR/HU/BG/KK/SR
-------------------------	--

Manual Language	EN/DE/FR/PL/CZ
------------------------	----------------

Dimension/Giftbox	495 x 230 x 290 mm
--------------------------	--------------------

Weight/Giftbox	11.8kg
-----------------------	--------

Pieces/Carton	1
----------------------	---

Pieces/Palette	42
-----------------------	----

Item Number	10120046
--------------------	----------

EAN	4260074975024
------------	---------------

Warranty	24 Month (except battery)
-----------------	---------------------------

Version: EN 13/01/2014

We reserve the right for technical changes and mistakes

Use UPS configurator on www.powerwalker.com for detailed backup time information.

PowerWalker is a brand of:

BlueWalker GmbH

Martin-Buber-Strasse 12 • D-41470 Neuss • Germany

Phone: +49 (0) 2137 / 92 98 73 • Fax: +49 (0) 2137 / 78 73 925

info@bluewalker.eu • www.bluewalker.eu • www.powerwalker.com

Available accessories



Yuasa 12V/7Ah battery
 Datasheet: [Link](#)
 CSB or Panasonic brand
 can also be used



Yuasa 12V/9Ah battery
 Datasheet: [Link](#)
 CSB or Panasonic brand
 can also be used



USB cable
 Item Nr.: 91010011



ATS (Automatic Transfer Switch)
 Datasheet: [Link](#)
 Item No.: 10120543



MBS (Maintenance Bypass Switch)
 Datasheet: [Link](#)
 Item No.: 10120500



Schuko Input -> IEC C13
 Item Nr.: 91010017



UK Input -> IEC C13
 Item Nr.: 91010029

Swiss Input -> IEC C13



IEC C13 -> IEC C14
 Item Nr.: 91010013



Schuko Input -> IEC C19
 Item Nr.: 91010018



UK Input -> IEC C19
 Item Nr.: 91010030

Swiss Input -> IEC C19



IEC C19 -> IEC C20
 Item Nr.: 91010028



IEC C13 -> IEC C20
 Item Nr.: 91010041



IEC C14 -> IEC C19
 Item Nr.: 91010040



IEC C14 -> Schuko
 Converter
 Item Nr.: 91015003



Schuko -> UK adaptor
 Item Nr.: 91010031