



- 1 5-Wege-Joystick-Navigation
- 2 Kensington Lock
- 3 2x HDMI (2.0b)
- 4 1x Display Port (1.4)
- 5 1x Kopfhörerausgang
- 6 Stromanschluss
- 7 1x USB 3.2 Gen 1 Typ B
- 8 3x USB 3.2 Gen 1 Typ A

Model	Oculux NXG253RDE
Introduction	<p>Optimiert für E-Sportler</p> <p>Der MSI Oculux NXG253RDE wurde gezielt für professionelles Gaming entwickelt. Das für den E-Sports gängige 24,5"-FHD-Display bietet nicht nur die Grundlage für maximale Übersicht und hohe FPS, sondern überzeugt auch mit kräftigen Farben dank Rapid-IPS-Technologie. Die extrem hohe Bildwiederholrate von 360 Hz und die rasante Reaktionsgeschwindigkeit von 1 ms GTG sorgen dafür, dass einem auch in hitzigen Gefechten nichts entgeht, während die NVIDIA G-SYNC-Technologie Screenshotting verhindert und für eine stets flüssige Bildwiedergabe sorgt. Außerdem unterstützt der Monitor den revolutionären NVIDIA Reflex Latency Analyzer - ein Tool zur Messung und Abstimmung der Systemlatenz.</p> <p>Damit auch nach mehrstündigen Gaming-Sessions die Kräfte nicht nachlassen, wurde beim Design des Monitors viel Wert auf Komfort und Ergonomie gelegt: Ausgestattet mit einem platzsparenden, vollständig justierbaren Standfuß, lässt sich der Monitor schnell und mühelos in die gewünschte Position bringen. USB-Steckplätze sind an der linken Monitorseite angebracht und jederzeit zugänglich. Und mit seinem rahmenlosen Design und der dezenten Mystic Light RGB-Beleuchtung fügt sich der Oculux NXG253RDE perfekt in jede Umgebung ein.</p>
Selling Points	<ul style="list-style-type: none"> • 360 Hz Bildwiederholrate für blitzschnellen Bildaufbau • 1 ms GTG Reaktionszeit sichert schlierenfreie Bilder • NVIDIA G-SYNC verhindert Screen-Tearing und sorgt für ein extrem flüssiges, verzögerungsfreies Gameplay • 24,5" Rapid-IPS-Monitor mit FHD-Auflösung (1920x1080) - perfekt für E-Sports • NVIDIA Reflex Latency Analyzer: Tool zur Messung der Systemlatenz • NVIDIA Ultra Low Motion Blur • Wide Color Gamut: Erweiterte Farbraumabdeckung für noch realistischere Farben • Ergonomischer Standfuß: Schnell und mühelos lässt sich der Monitor perfekt an die individuelle Sitzhaltung anpassen • HDR Ready • Mystic Light RGB-Beleuchtung für den perfekten Gaming-Look • Die ideale Ergänzung zu MSI Gaming-PCs und Komponenten • Schlicht und stilvoll im rahmenlosen Design
Bilder und Logos	Produktanlage Oculux NXG253RDE

Model	
SKU Number	9S6-3BB07T-002
Brand	MSI
Series Name	Gaming
MKT Name	Oculux NXG253RDE
Color	ID1/Black-Black
Local Dimming	NA
Display	
Screen Size	24.5" (62.2cm)
Active Display Area (mm)	543.168(H) x 302.616(V)
Curvature	Flat
Panel Type	Rapid IPS
Resolution	1920x1080 (FHD)
Pixel pitch	0.2829(H)x0.2802(V)
Aspect Ratio	16:9
Dynamic Refresh Rate technology	G-SYNC
HDR (High dynamic range)	HDR400
SDR Brightness (nits)	400
Contrast Ratio	1000:1
DCR (Dynamic Contrast Ratio)	NA
Signal Frequency	150.9~417.6 KHz(H) / 48~360 Hz(V)
Refresh Rate	360Hz
Response Time (MPRT)	1ms (ULMB)
Response Time (GTG)	1ms
Response Time (Tr + Tf)	NA
View Angles	178°(H)/178°(V)
NTSC (CIE1976 area percentage/overlap)	95.85%/80.24%
NTSC (CIE1931 area percentage/overlap)	78.7%/74.04%
sRGB (CIE1976 area percentage/overlap)	109.63%/98.04%
sRGB (CIE1931 area percentage/overlap)	111.12%/98.94%
Adobe RGB (CIE1976 area percentage/overlap)	93.97%/85.47%
Adobe RGB (CIE1931 area percentage/overlap)	82.37%/77.02%
DCI-P3 (CIE1976 area percentage/overlap)	87.31%/84.09%
DCI-P3 (CIE1931 area percentage/overlap)	81.91%/81.2%
Rec.709 (CIE1976 area percentage/overlap)	95.85%/80.24%
Rec.709 (CIE1931 area percentage/overlap)	78.7%/74.04%
Surface Treatment	Anti-glare
Touch Screen	Non-touch
Display Colors	1.07B
Color bit	10 bits (8 bits + FRC)
Note DP	1920 x 1080 (Up to 360Hz)
Note HDMI	1920 x 1080(Up to 240Hz)
Note DVI	N/A
I/O Ports	
HDMI	2
HDMI version	2.0b

HDMI HDCP version	NA
DisplayPort	1
DisplayPort version	1.4
DisplayPort HDCP version	NA
Thunderbolt	NA
Thunderbolt version	NA
Thunderbolt HDCP version	NA
USB Type C (DisplayPort Alternate)	NA
DVI	NA
D-Sub	NA
Mic-in	NA
Mic-in upstream	NA
Headphone-out	1
Audio Combo	NA
USB 2.0 Type A	NA
USB 2.0 Type B	NA
USB 2.0 Type C	NA
USB 3.2 Gen 1 Type A	3
USB 3.2 Gen 1 Type B	1
USB 3.2 Gen 1 Type C	NA
USB 3.2 Gen 2x2 Type C	NA
USB 3.2 Gen 2x2 Type A	NA
Card reader	NA
Lock type	Kensington Lock
Power	
Country	DE
Territory	EU
Entity	DE
Power Type	External Adaptor 20V 4.5A
Power Input	100~240V, 50/60Hz
Warranty	
Warranty	3 Jahre Pick Up & Return
Design	
Adjustment (Tilt)	-5° ~ 20°
Adjustment (Swivel)	-45° ~ 45°
Adjustment (Height)	0 ~ 130 mm
Adjustment (Pivot)	-90° ~ 90°
VESA Mounting	100x100mm
Frameless Design	Yes
Inside Carton Dimension (WxDxH)	
Inside Carton Dimension (WxDxH) (mm)	761 x 207 x 410
Inside Carton Dimension (WxDxH) (inch)	29.96 x 8.15 x 16.14
Outer Carton Dimension (WxDxH)	
Outer Carton Dimension (WxDxH) (mm)	776 x 222 x 435
Outer Carton Dimension (WxDxH) (inch)	30.55 x 8.74 x 17.13
Product Dimension with Stand (WxDxH)	
Product Dimension with Stand (WxDxH) (mm)	560.1 x 233.7 x 399.3
Product Dimension with Stand (WxDxH) (inch)	22.05 x 9.2 x 15.72
Product Dimension without Stand (WxDxH)	
Product Dimension without Stand (WxDxH) (mm)	560.1 x 64.3 x 335.5
Product Dimension without Stand (WxDxH) (inch)	22.05 x 2.53 x 13.21
Stand Dimension (WxDxH)	
Stand Dimension (WxDxH) (mm)	303.3 x 233.7 x 416.7
Stand Dimension (WxDxH) (inch)	11.94 x 9.2 x 16.41
Weight	
Weight (Net kg)	6.47
Weight (Net lbs)	14.26
Weight (Gross kg)	9.02
Weight (Gross lbs)	19.89
Feature	
Feature	Gaming Mode 5 Ways Joystick Navigator Control Frameless design HDR Ready G-Sync
Accessories	
DisplayPort Cable	1
HDMI Cable	1
DVI Cable	0
USB Type A to Type B Cable	1
USB Type C to Type A Cable	0
USB Type C to Type C Cable	0
Thunderbolt Cable	0
VGA Cable	0
3.5mm audio Cable	0
3.5mm combo audio Cable	0
Power Cord	1
AC Adaptor	1
Quick Guide	1
Warranty Card	1
Barcode Info	
EAN	4719072744373
UCC14	10824142222604
UPC	824142222607
JAN	