

UPS-2103, Volta Online UPS 3KVA/3000W

Product Images



Short Description

- True double-conversion design with high adaptability to harsh
- mains conditions.
- Real PF 1 can provide more power in same space High efficiency results in energy saving
- Adjustable charging current and flexible battery configuration
- Optimized charging method to expand battery life time.
- Built-in OVCD protection, fan lock detection, over temperature detection, overload warning to enhance the product reliability
- Dot matrix LCD support up to 10 languages for easy installation and
- service.
- Embedded Ethernet port solution provide safe network connection to
- Cloud which will meet the increasing IoT trend
- Mobile APP for monitoring, configuration. Support Android/iOS
- USB HID enable monitoring on UPS without software installation
- Dry contactor for industrial condition
- Upgraded network card compliance with IEC standard cybersecurity
 - True double-conversion design with high adaptability to harsh
 - mains conditions.
 - Real PF 1 can provide more power in same space High efficiency results in energy saving

- Adjustable charging current and flexible battery configuration
- Optimized charging method to expand battery life time.
- Built-in OVCD protection, fan lock detection, over temperature detection, overload warning to enhance the product reliability
- Dot matrix LCD support up to 10 languages for easy installation and service.
- Embedded Ethernet port solution provide safe network connection to Cloud which will meet the increasing IoT trend
- Mobile APP for monitoring, configuration. Support Android/iOS
- USB HID enable monitoring on UPS without software installation
- Dry contactor for industrial condition
- Upgraded network card compliance with IEC standard cybersecurity

Description

The LevelOne Online UPS is the ultimate solution for dependable battery backup in both home and office settings. With an output power factor of 1.0, this UPS delivers maximum efficiency and performance. Designed for generator compatibility, it provides continuous power even during extended outages. Equipped with a HID-compatible USB connection for seamless device communication and an Emergency Power Off (EPO) port for added safety during emergencies, the UPS offers both convenience and security. The easy battery replacement feature simplifies maintenance, while the programmable outlet management allows you to tailor power distribution to meet your specific needs. Easy to install and operate, the LevelOne Online UPS provides a reliable and efficient way to protect your systems from power surges and failures, ensuring the uninterrupted operation of your critical equipment. The included rackmount ears support both rack mounting and tower installation, offering flexibility in setup.

Additional Information

Code des Harmonisierten Systems (HS)	850440
Zolltariflicher Warencode (TARIC)	8504406090
Farbe	Schwarz
EAN	4015867235034
Modellnummer	UPS-2103
Zulassungen und Konformität	CE/FCC/RoHS/IP20 IEC/EN 61000-4-2 IEC/EN 61000-4-3 IEC/EN 61000-4-4 IEC/EN 61000-4-5
Operating humidity	0% RH ~ 90% RH
Operating temperature	0°C ~ 40°C
Lieferumfang	USB cable Power cord User Manual Tower feet Rack ears QIG EcDoc
Dimensions (W x D x H)	600*438*85.5
Produktgewicht (kg)	26.3
Alarm	Battery Mode, Low Battery, Overload, Fault
Batteriekapazität (mAh)	6 x 12V/9Ah
Batteriekapazität (Wh)	108
Batterietyp	Lead-acid
Battery voltage	72V
Switches/Buttons	Power On/Off
Anzeige	Graphic LCD
Number of battery	6
Port Configuration	IEC C13 x 8, IEC C19 x1 RJ45 x 2, USB x 1, HDMI x 1 ,RS-232,Terminal block
Eingangsspannung	VAC 160-300V
Ausgangsspannung	VAC200-240,50Hz/60Hz
Power rating	3000VA
USV-Typ	Online double conversion

Waveform	Sine wave
Schutzart	Emergency Power Off (EPO) Port
Wiederaufladezeit	VAC 220/1.5A, 3h to 90%

