


STRONG



UNIVERSAL WI-FI REPEATER 300 REPEATER300S

Boost your Wi-Fi network!



4 Years warranty

Looking for a solution to enhance Wi-Fi signals specific areas of your home?

Introducing the REPEATER300S from STRONG: Boost your Wi-Fi coverage effortlessly with our latest innovation. With a maximum speed of 300 Mbps, this compact wall plug solution ensures seamless coverage throughout any space. Equipped with 2 adjustable external antennas and a smart LED system, it gets easier placing at home the repeater for optimal performance. Upgrade your Wi-Fi experience with the REPEATER300S from STRONG.

Performance



- Supports 802.11n/b/g standards
- 300 Mbps @ 2.4 GHz
- Works with any standard modem or router

Coverage & Reliability



- 2x adjustable external antennas for maximum coverage and reliability
- Smart LED system for an optimum positioning of the repeater: LAN, Power, 3 x Wi-Fi signal strength

Security



- WPA-PSK/ WPA2-PSK encryption for the highest level of Wi-Fi security
- Connect & Secure button for an easy set up and a maximum network security
- Power on/off button

Connections



- 1x Ethernet LAN port to connect any computer, set-top-box, Smart TV, game console, ...



UNIVERSAL WI-FI REPEATER 300

REPEATER300S

Wi-Fi

Frequency	2.4 GHz
Standards	IEEE 802.11b/g/n
Signal Rate	Up to 300 Mbps
Security	WPA-PSK/ WPA2-PSK encryption
Antenna	2x 3 dBi omnidirectional, adjustable
Transmit Power	Europe: <20 dBm (2.4 GHz)
Supported Channels	1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13
Features	Enable/Disable, Client Isolation

Hardware

Ethernet Ports	1x 10/100 Mbit/s LAN port (Auto MDI/MDIX)
Buttons	Connect & Secure (WPS)
LEDs	LAN, Power, 3 x Wi-Fi signal strength
Power	Internal, 100-240 V, 50/60 Hz, 0.1 A
Standards	IEEE 802.11b/g/n

Software

Configuration Wizards	Repeater
WAN Type	Dynamic IP, Static IP, PPPoE
DHCP	Auto, Server, Client

Management


Web User Interface, Time Settings, Configuration Backup/Restore, Firmware Upgrade

Internet Protocol

IPv4

Other specifications

Certification	CE
Package contents	1x Universal Wi-Fi Repeater 300 1x Installation instructions
System requirements	Windows 7, 8, 8.1, 10, Mac OS X, Linux, Internet Browser
Environment	Operating temperature: 0° C ~ +40° C Storage temperature: -10° C ~ +70° C Operating humidity: 10%~90% non-condensing Storage humidity: 10%~90% non-condensing
Size (WxDxH):	57 x 82,7 x 78,7 mm
Size with antenna (WxDxH):	57 x 82,7 x 141 mm
Weight:	88.1g



REPEATER300S EAN: 9120072378126
PCB: 20