

47527103

SCHUKO socket outlet with hinged cover Labelling field, enhanced contact protection, Berker K.5, Aluminium, aluminium anodised

Technical features

Architecture

Design	according to DIN 49440

Main electrical features

Nominal voltage	250 V
Rated current	16 A
Rated voltage	250 V AC

Cover, door

- when opening hinged cover, it can be arrested in end position
- Central cover plate

Materials

RAL colour	RAL 9006 - White aluminium
Colour of design line	Aluminium
Colour	aluminium optics
Colour	aluminium
Material / workmanship	aluminium, anodised
Material	Aluminium
Surface appearance	matt

Dimensions

Insertion depth	32 mm

Installation, mounting

- with spreader claws

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1

- with plug-in terminals

Use

- Labelling field
- enhanced contact protection

Safety

Protection index IP	IP20
IK protection code against mecanical impacts	07
Enhanced contact protection (child protection)	according to IEC 60884-1
Enhanced contact protection (child protection)	according to VDE 0620-1

- Enhanced contact protection

Identification

Main design line	Berker K.5
Secondary design line(s)	Berker K.5

Instructions

- Labelling field height arranged for 6 mm P-touch strips.

  Specially suited to combinations of several socket outlets if right angle plugs are used.