HEDLER®
Systemlicht

HEDLER LED1000 - technical data

HEDLER Profilux LED1000 - technical data

Code	< 5056 >
AC power supply	110 - 230 V / 50 - 60 Hz
single cell LED	185 W high power
average lifetime LED	approx. 50000 hours
CRI of bulb	> 95
Kelvin - bulb	approx. 5600 K
spot lighting position - angle of light beam without reflector	approx. 20° (primary)
flood lighting position - angle of light beam without reflector	approx. 60° (primary)
fuse	electronic
ambient temperature	-15° up to +40° C
material of housing	aluminium
fan cooling - manual	yes
fan cooling - automatic	yes
cooling	fan
attachment to light stand	bush 5/8“
weight	3300 gr
measurements w/o U-bracket length x width x height	250 x 165 x 180 mm
length of power cord	3 m
suits for original sound recording	yes
incorporated electronic ballast	yes
thermo-safety-switch electronic ballast	yes
integrated overheating protection	yes
integrated LED safety switch-off	yes
integrated operation-hour counter	yes
certification(s)	CE

Hedler reserves the right to make technical alterations without prior notice. Errors and mistakes are excepted. If more information about Hedler equipment is needed, please contact your dealer or Hedler Systemlicht GmbH, Heerstrasse 112, D-65594 Runkel, www.hedler.com directly.