

PRODUCT NO. 4733-0FW110

**DOTLUX Tracklight STICKtrack 30W 1,2m COLORselect white**



to the product page

- One part number - three light colors adjustable by COLORselect
- Natural color perception due to extra high CRI>95 value
- Compact design, ideal for low room heights
- Uniform light distribution for optimum ambient lighting
- Benefit from the large-area illumination of a light band with simple installation in your track rail

<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	110°
<b>WEIGHT IN KG</b>	0.718	<b>PROTECTION CLASS (IP)</b>	IP20
<b>POWER CONSUMPTION IN WATTS</b>	30	<b>LIGHT COLOR</b>	multicoloured
<b>NET LUMINOUS FLUX IN LUMENS</b>	max. 3060	<b>INPUT VOLTAGE</b>	176 - 240 V AC/DC
<b>LUMEN PER WATT</b>	102	<b>SERVICE LIFE</b>	approx. 50.000 h at 25°C
		<b>COLOR TEMPERATURE IN KELVIN</b>	3000/4000/5700
		<b>COLOR-RENDERING-INDEX</b>	CRI > 95
		<b>POWER FACTOR</b>	0,9
		<b>INRUSH CURRENT IN A</b>	0
		<b>LUMEN PER WATT</b>	102
		<b>PROTECTION CLASS</b>	I
		<b>SUITED FOR EMERGENCY LIGHTING</b>	yes
		<b>WARRANTY IN YEARS</b>	3
		<b>SIMILAR TO RAL-COLOUR</b>	9016
		<b>ASSORTMENT</b>	Proline
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>ETIM GRUPPEN-ID</b>	EC001744
		<b>DIMMING 0-10 V</b>	No
		<b>DIMMING 1-10 V</b>	No
		<b>DIMMING DALI</b>	No
		<b>DIMMING DMX</b>	No
		<b>DIMMING DSI</b>	No
		<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
		<b>DIMMING LINESWITCH</b>	No
<b>Dimensions</b>			
<b>length:</b>	1240mm		
<b>width:</b>	32mm		
<b>height:</b>	52mm		

<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
<b>SUITABLE FOR EMERGENCY LIGHTING</b>	Yes
<b>COLOUR OF LIGHT ADJUSTABLE</b>	Positions
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>PULSE DURATION IN <math>\mu</math>S</b>	0
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	F