



4011 Sprossenanlegeleiter

S

- › Leiterinnenbreite 300 mm.
- › Holme aus nahtlosen Strangpressprofilen mit ergonomischer Form.
- › Sprossen aus Walzprofil.
- › Mit Holm verpresste Leiterfüße.



Sprossenzahl		6	8	10	12	14	16	18
Holm	ca. mm	60	60	60	60	60	66	66
Länge	ca. m	1,78	2,34	2,90	3,46	4,02	4,58	5,14
Standhöhe	ca. m	0,75	1,29	1,83	2,37	2,91	3,45	3,99
Arbeitshöhe	ca. m	2,25	2,79	3,33	3,87	4,41	4,95	5,49
Reichhöhe	ca. m	2,75	3,29	3,83	4,37	4,91	5,45	5,99
Breite	ca. mm	355	355	355	355	355	355	355
Gewicht	ca. kg	2,9	3,7	4,6	5,5	6,4	7,7	8,4
EAN-Code		4019502338975	4019502338982	4019502338999	4019502339002	4019502339019	4019502339026	4019502339033
Best.-Nr.		401106	401108	401110	401112	401114	401116	401118

Erläuterung zu Stand-, Arbeits- und Reichhöhe siehe Seite 5.

Empfohlenes Zubehör:



S. 176

Traverse
für Leiterteil



S. 177

Einhängehakenset



S. 177

Aufhängungsset