

Combining a massive six heatpipe dual radiator design with an exquisite NF-P14/NF-P12 dual fan configuration, the NH-D14 is built for ultimate quiet cooling performance. Topped off with a tube of Noctua's award-winning NT-H1 thermal compound as well as the new SecuFirm2™ multi-socket mounting system, the NH-D14 is an elite choice for the highest demands in premium quality quiet cooling.

Socket compatibility	Intel LGA1366, LGA1156, LGA775 & AMD AM2, AM2+, AM3 (backplate required)
Weight (with fan)	1070 g (1240 g with 2 fans)
Material	Copper (base and heat-pipes), aluminium (cooling fins), soldered joints & nickel plating
Fan compatibility	140x140x25 & 120x120x25mm

NF-P14 Specifications



Size	140 x 140 x 25 mm	
Bearing	SSO-Bearing	
Blade Geometry	NF-P14 Blade Design with VCN	
Input Power	1.2 W	
Input Current	0.1 A	
Voltage Range	12 V	
MTBF	> 150.000 h	

NF-P14	Fan	with U.L.N.A.
Rotational Speed +/-10%	1200 RPM	900 RPM
Airflow	110.3 m³/h	83.7 m³/h
Acoustical Noise	19.6 dB(A)	13.2 dB(A)
Static Pressure	1.29 mmH ₂ O	0.77 mmH ₂ O

NF-P12 Specifications

Size	120 x 120 x 25 mm	
Bearing	SSO-Bearing	
Blade Geometry	Nine Blade Design with VCN	
Input Power	1.08 W	
Input Current	0.09 A	
Voltage Range	12 V	
MTBF	> 150.000 h	

NF-P12	Fan	with U.L.N.A.
Rotational Speed +/-10%	1300 RPM	900 RPM
Airflow	92.3 m³/h	63.4 m³/h
Acoustical Noise	19.8 dB(A)	12.6 dB(A)
Static Pressure	1.68 mmH ₂ O	1.21 mmH ₂ O



Product Noctua NH-D14

Packaging Type Pcs./Colli

Retail **8**

Warranty
6 years

Scope of Delivery

- 1x NF-P14 premium fan
- 1x NF-P12 premium fan
- 2x Ultra-Low-Noise Adaptor (U.L.N.A.)
- Y-Split Cable
- NT-H1 Thermal Compound
- SecuFirm2™ Mounting Kits