



INTRATEC
100% SHOPPING

**Datasheet
Main switch
Art. No. MKDGH36-01**

Intratec Warenhandels GmbH

Gruetzmuehlenweg 46
22339 Hamburg
Germany

FON: +49 40 538092 888

FAX: +49 40 538092 930

MAIL: info@intratec-hh.de

WEB: www.intratec-shop.de



Electrical specifications

Service voltage: 400V AC

For installation of devices up to max. 63A

Protection class: IP65

Protected against: Water jets and splashes from all directions, high humidity and water vapour

Areas of application: Outdoors (e.g. garden) and damp rooms such as cellars, garages or bathrooms, water-exposed areas in industry that are frequently cleaned with high-pressure cleaning, for example

Material housing: acrylic ester styrene acrylonitrile (ASA)

Color housing: gray RAL 7035

Material door: PC Polycarbonate

Color door: Transparent

Glow wire test: 650°C

Temperature resistance: -25°C to +60°C (thus always reliable even in cold storage, outdoor use in winter and at high temperatures such as direct sunlight)

Manufactured according to DIN IEC60670 / IEC 60228

Halogen free, RoHS compliant, CE, UV stable

Optional lock with key

Pre-stamping for cable glands: Up to 12 modules: M20, M25, M32, From 12 modules up to M40

With built-in DIN top-hat rail for all standardized circuit breakers / RCDs according to DIN 43880

Finger-safe N/PE terminal strip

Mounting material / Installation instructions

Dimensions:

A: 508 mm

B: 319 mm

C: 144 mm

D: 125 mm

E: 210 mm

F: 380 mm

