

OVERVIEW



1. Power button	4. USB-C 3.2 Gen 1
2. USB 3.2 Gen 1 (Always On)	5. USB-C 3.2 Gen 1
3. Headphone / microphone combo jack (3.5mm)	

PERFORMANCE

Processor

Processor Family

AMD Ryzen™ 5 / 7 Processor

Processor

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
AMD Ryzen 5 5600U	6	12	2.3GHz	4.2GHz	3MB L2 / 16MB L3	LPDDR4-4266	AMD Radeon™ Graphics
AMD Ryzen 7 5800U	8	16	1.9GHz	4.4GHz	4MB L2 / 16MB L3	LPDDR4-4266	AMD Radeon Graphics

Operating System

Operating System

- Windows® 10 Pro 64
- Windows 10 Home 64
- Windows 11 Pro 64
- Windows 11 Home 64

Graphics

Graphics

Graphics	Type	Memory	Connector	Max Resolution	Key Features	Remark
AMD Radeon Graphics	Integrated	Shared	-	-	DirectX® 12	-

Monitor Support

Monitor Support

Supports up to 3 independent displays via native display and 2 external monitors; supports external monitors via USB-C (up to 3840x2160@60Hz)

Chipset

Chipset

AMD SoC (System on Chip) platform

Memory

Max Memory^[1]

- 8GB soldered memory, not upgradable
- 16GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots, dual-channel

Memory Type

LPDDR4x-4266

Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

Storage

Storage Support

One drive, up to 256GB M.2 2242 SSD or 1TB M.2 2280 SSD

Storage Slot

One M.2 2280 PCIe Gen 3x4 slot, supports M.2 2242/2280 SSD

Storage Type

Disk Type	Interface	RPM	Offering	Security
-----------	-----------	-----	----------	----------

M.2 2242 SSD	PCIe NVMe, PCIe 3.0 x4	-	256GB	-
M.2 2280 SSD	PCIe NVMe, PCIe 3.0 x4	-	512GB / 1TB	-

Removable Storage

Optical

None

Multi-Media

Audio Chip

High Definition (HD) Audio

Speakers

2 front-facing speakers, 2W x2, optimized with Dolby® Atmos®, Smart AMP

Microphone

Dual array microphone, support WoV (Wake-on-Voice)

Camera

1.0-megapixel RGB, 720p, with privacy shutter, fixed focus

Sensor

Sensors

- Accelerometer (G) sensor
- Ambient light sensor (ALS)

Battery

Battery

Integrated Li-Polymer 71Wh battery, supports Rapid Charge Express (get 3 hours of runtime with a 30-minute charge)

Max Battery Life^[1]

- Local video (1080p) playback@150nits: 20.4 hr
- MobileMark® 2014: 27.05 hr
MobileMark 2018: 15.68 hr

Notes:

1. All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, and/or JEITA 2.0 battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter

65W USB-C (3-pin) AC adapter

DESIGN

Display

Display^[1]

Size	Resolution	Touch	Type	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle	Key Features
14.0"	FHD (1920x1080)	Multi-touch	IPS	300 nits	Glossy	16:9	-	72% NTSC	-	AAR 89%, DC dimmer, Dolby Vision™

Touchscreen

GF2 or OGM (One Glass Metal mesh) Direct Bonding, capacitive-type multi-touch, supports 10-point touch

Multi-mode

Laptop, tent, stand and tablet modes supported by 360° hinge

Notes:

1. California Electronic Waste Recycling Fee
In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product.
For more information, go to <https://www.calrecycle.ca.gov/Electronics/Consumer>

Input Device

- Pen
- Lenovo Digital Pen with replaceable AAAA alkaline battery, 4096 levels of pressure sensitivity
 - Lenovo Digital Pen without replaceable AAAA alkaline battery, 4096 levels of pressure sensitivity
 - No pen (pen sold separately)

Keyboard

6-row, multimedia Fn keys

Keyboard Backlight

LED backlight

Mechanical

Dimensions (WxDxH)

Models	Dimensions
All models	320.4 x 214.6 x 15.68-17.7 mm (12.61 x 8.44 x 0.61-0.69 inches)

Weight^[1]

Models	Weight
All models	1.45 kg (3.20 lbs)

Case Color

Slate grey

Surface Treatment

Aluminium anodizing stamping

Case Material

Aluminium (top), aluminium (bottom)

Notes:

1. The system weight varies depending on configurations

CONNECTIVITY

Network

WLAN + Bluetooth®

Wi-Fi® 6, 802.11ax 2x2 Wi-Fi + Bluetooth 5.0

Ports^[1]

- Standard Ports^[2]
- 1x USB 3.2 Gen 1 (Always On)
 - 2x USB-C 3.2 Gen 1 (support data transfer, Power Delivery 3.0 and DisplayPort™ 1.4)
 - 1x Headphone / microphone combo jack (3.5mm)

Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.
USB 2.0: 480 Mbit/s;
USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
Thunderbolt™ 3: 40 Gbit/s;
FireWire 400: 400 Mbit/s;
FireWire 800: 800 Mbit/s

2. Depending on many factors, actual data transfer speed may be lower than theoretical speed

Monitor Cable

Monitor Cable

- Lenovo USB-C 3-in-1 Hub (USB-C to VGA / HDMI® / USB-A)
- No monitor cable

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in chipset

Fingerprint Reader

Touch style fingerprint reader on palm rest

BIOS Security

- Administrator password
- User password
- Master hard disk password
- User hard disk password

Other Security

Camera privacy shutter

SERVICE

Warranty

Base Warranty

- 1-year depot service
- 1-year depot with 2-year system board service
- 2-year (1-yr battery) depot service

ENVIRONMENTAL

Operating Environment

Temperature^[1]

- At altitudes up to 2438 m (8,000 ft)
 - Operating: 5°C to 35°C (41°F to 95°F)
 - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
 - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

1. When you charge the battery, its temperature must be no lower than 10°C (50°F)

CERTIFICATIONS

Green Certifications

Green Certifications


- ENERGY STAR® 8.0
- ErP Lot 3
- RoHS compliant



AMD



AMD



AMD



AMD



AMD



AMD