

DIGITUS Wall Mounting Cabinets Dynamic Basic Series - 600x450 mm (WxD)

DN-19 07-U-EC-SW EAN 4016032257783





7U wall mounting cabinet 416x600x450 mm, color black (RAL

The Wall Mounting Cabinets of the Dynamic Basic Series are made of a robust steel construction. Stability is given due to the welding spots. The side sections are detachable and the installation on the wall is easy so it can be implemented quickly. Due to their flexibility the cabinets are ideal for all current IT and telecommunication applications.

- Safety class rating IP20
- Lockable safety-glass door with steel frame
- 210° door opening angle
- 1-point-locking-mechanism on the front door
- 483 mm (19") profile rails mounted on the front side inside of the cabinet, galvanized
- 483 mm (19") profile rails are adjustable in depth and with height
- 0.8 1.2 mm strong sheet steel with high load capacity, powder
- Cable entry on the rear side, roof and base (pre-punched break-outs)
- Roof is prepared for fan units (punched out entries)
- Ventilation slots for active and passive ventilation and exhausting

- 4 earthing points (base, side panel and front door) with protection cap
- Colour: Black
- Width: 600
- Model: With permanent frame
- Height: 416
- Depth: 450
- RAL-number: 9005
- Number of doors: 1
- Type of ventilation: Passive
- Material: Steel
- Number of height units: 7
- With socket: no
- Degree of protection (IP): IP20
- Type of surface: With powder coating
- Mounting level: Front side
- Type of profile rail: L-shaped
- With roof plate: yes
- With earthing: no
- With front door: yes With backside door: no
- With sidewall: yes
- Demountable: no
- Modular spacing: 482.6 mm (19 inch)

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	19.50	66.00	54.00	46.50	165,726.00
Packaging Unit Inside	1	19.50	0.00	0.00	0.00	0.00
Packaging Unit Single	1	19.50	66.00	54.00	46.50	165,726.00
Net single without Packaging	1	19.50	66.00	54.00	46.50	165,726.00



More images:











