BUSCH-JAEGER



Dome camera External analogue camera for the door intercom.

Functions at a glance

- Image Sensor: 1/3" 1.3MP SONY Exmor CMOS.
- Effective Pixels: 1305(H)×1049(V).
- Resolution: 700.
- Horizontal detection angle: 30° - 90° (manually adjustable)
- S/N Ratio: ≥50 dB
- Min. Illumination (Day): 0.1 Lux @ F2.0
- Min. Illumination (Night): 0 Lux @ F2.0
- Video signal: 1 x CVBS, 1Vpp, 75 Ohm (Cinch)
- White Balance: AWB, 1800 – 10800
- DNR: 2D DNR, 3D DNR
- Zoom: 1X-8X
- Lens: 2.8-12 mm
- IR Range: 40 m
- Input Voltage: DC 12 V +/- 10 % (e.g. ABB CP-D 12/0.83 or CP-D 12/2.1)
- Rated current: 350 mA
- Power Consumption: <4.5 W
- Weight: 490 g
- Protection class (Device): IP 66
- Temperature range (Device): -20 °C to +60 °C
- Operation humidity: <85 %
- Dimensions: (D x H) 119 x 104 mm
- 40 cm preassembled cable with connecting plugs.
- A connection unit is required for the installation (not included in the scope of supply. e.g. Spelsberg 33441201).

Order details

Article No.:	83550/2
Order No.:	2CKA008300A0488
EAN:	4011395222621
Customs tariff number:	85177900
Price group:	23
Price:	567,00 EUR plus VAT

Downloads

Instruction manual

» Installation and operating instructions
» Product manual

Certificates

» EU-declaration of conformity
» ROHS product declaration