

Großes und elegantes professionelles 4K Signage- Display

TH-86SQ1

Ausgerüstet mit fortschrittlichen professionellen Funktionen bietet es eine schlanke, leichte und skalierbare Lösung, die jegliche Installationen erleichtert. 4K Ultra HD-Panel mit 86", Intel® Smart Display Module (Intel® SDM), Dauerbetrieb, Hochformat, 4K Digital Link, schmaler Rahmen



KEY FEATURES

- 4K IPS-Panel mit 86" und 500 cd/m2 mit schlankem und elegantem Design für Dauerbetrieb
- Hohe Bildqualität durch HDR-Unterstützung (HLG-System), sodass helle und dunkle Bilder auf realistische Weise angezeigt werden
- 4K-USB-Media-Player: externe Geräte werden überflüssig und Updates über LAN ermöglicht
- Umfassende Erweiterbarkeit mit extrem schmalen Intel® SDM (Intel® Smart Display Module), DisplayPort-Anschluss für Daisy-Chain-Signage, Unterstützung von mehreren Bildschirmen (Quad, PinP, PbyP) und 4K DIGITAL LINK
- Flexible und leichte Installation entweder im Hoch- oder Querformat

Großes, professionelles und elegantes 4K-Signage-Display. Ausgerüstet mit fortschrittlichen und professionellen Funktionen bietet es eine schlanke, leichte und skalierbare Lösung, die jegliche Installationen erleichtert.



SPECIFICATIONS

Screen size (diagonal) (inch)	86-inch (2174 mm)
Screen size (diagonal) (mm)	2174 mm
Aspect Ratio	16:9
Panel Type	IPS Panel / Edge-LED
Effective display area (W x H) (mm)	1895.0 x 1065.9 mm
Effective display area (W x H) (inch)	74.6 x 41.9 inch
Auflösung	3840 x 2160
Brightness (typ.)	500 cd/m ²
Contrast Ratio	1200:1 (Typ)
Response Time	8 ms (G to G)
Terminals HDMI In	HDMI TYPE-A Connector x 2
Terminals DisplayPort IN	DisplayPort x 1
Terminals DisplayPort OUT	DisplayPort x 1
Terminals DVI-D IN/AUDIO IN (L/R)	DVI-D 24-pin x 1/ Stereo Mini Jack (M3) x 2 (Shared with PC In)
Terminals PC IN/AUDIO IN (L/R)	Mini D-sub 15-pin x 1/ Stereo Mini Jack (M3) x 2 (Shared with DVI-D In)
Terminals USB	USB Connector (TYPE A) x 2, DC 5 V/2 A (USB 3.0 supported)
Terminals Serial	D-sub 9-pin x 1, RS232C Compatible
Terminals IR IN / OUT	Stereo Mini Jack (M3) x 1 / x 1
Built-in Speaker	20 W [10 W + 10 W]
Power Requirements	110-127 V AC, 50/60 Hz, 220-240 V AC, 50/60 Hz
Power Consumption	480 W
Power Off Condition	Approx. 0.3 W
Stand-by Condition	Approx. 0.5 W
Dimensions (W x H x D) (mm)	1928 x 1099 x 86 mm
Dimensions (W x H x D) (inch)	75.9" x 43.3" x 3.4"
Carton Size (W x H x D) (mm)	2224 x 1427 x 373 mm
Carton Size (W x H x D) (inch)	87.6" x 56.2" x 14.7"
Bezel width (mm)	15.2 mm (T/B/L/R)
Bezel width (inch)	0.60 inch (T/B/L/R)
Operating Time	24 h/day
Operating Environment	Temperature : 0 °C to 40 °C / Humidity: 20% to 80% (Non-condensation)
Weight (kg)	Approx. 66.0 kg
Weight (lbs.)	Approx. 145.5 lbs
Wall-hanging pitch (inch)	23.6" x 15.8" VESA Compliant
Viewing angle [(T/B)/(L/R)]	178°/178° (CR≥10)
Terminals Audio Out	30 W [15 W + 15 W] 10% THD
Wall-hanging pitch (mm)	600 x 400 mm VESA Compliant

Terminal DIGITAL LINK	RJ45 x 1, 100 BASE-TX, Compatible with long reach mode and PLink™
Terminal LAN	RJ45 x 1, 10 BASE-T / 100 BASE-TX, Compatible with PLink™
Operating Environment Humidity	0 °C to 40 °C (32°F to 104°F) Altitude 0~1400 m (4593 ft)/0 °C to 35 °C (32 °F to 95 °F) Altitude 1400 ~2800 m (4593 ft to 7874 ft)
Operating environment Temperature	20% to 80% (Non-condensation)
Orientation	Landscape/Portrait (Angle adjustment is not possible for portrait installation.)
Tilting angle	0-20 degrees forward/backward with landscape/portrait setting
Terminals Slot	Intel® SDM specification Corresponding size SDM-S / SDM-L, Supply power 12 V / 5.5 A, 3.3 V / 1.1 A

URL: <https://business.panasonic.de/visuelle-systeme/th-86sq1>

CONTACT

Web: <https://business.panasonic.de/visuelle-systeme/contact-us>