

47526049

SCHUKO socket outlet with hinged cover and "ZSV" imprint in orange Labelling field, enhanced contact protection, Berker Q.1/Q.3/Q.7/Q.9, polar white velvety

Technical features

Architecture

Design	according to DIN 49440
Technical version	Imprint "ZSV" in orange

Main electrical features

Nominal voltage	250 V
Rated current	16 A
Rated voltage	250 V AC

Cover, door

- with self-closing hinged covers
- Central cover plate

Materials

RAL colour	RAL 9010 - Pure white
Colour of design line	polar white
Colour	white
Colour	polarwhite
Material	duroplastic
Surface appearance	velvety

Dimensions

Insertion depth	32 mm

Installation, mounting

- with spreader claws

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1

- with plug-in terminals

Use

- Labelling field
- enhanced contact protection

Safety

Protection index IP	IP20
IK protection code against mecanical impacts	02
Enhanced contact protection (child protection)	according to IEC 60884-1
Enhanced contact protection (child protection)	according to VDE 0620-1

- Enhanced contact protection

Identification

Application, usage	Flush-mounted wet-room installation
Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.3, Berker Q.1

Instructions

- Labelling field height arranged for P-touch strips 6 mm.