

# AGV 17-125 XE DMS | 1750 W angle grinder with AVS



- Powerful, 1750 W PROTECTOR-MOTOR with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool.
- Constant power electronics with soft start for smooth start up.
- Line lock out function to prevent automatic start up after power breakdown.
- Thermal overload protection to prevent overheating.
- Safety clutch to protect the user from kickback injuries.
- FIXTEC™ nut for tool-free disc change.
- Burst resistant and tool-free safety guard for best user protection and fast adjustment.

| AGV 17-125 XE DMS                        |                                                                                       |
|------------------------------------------|---------------------------------------------------------------------------------------|
| Anti-kickback protection                 | Yes                                                                                   |
| AVS Anti-Vibration System                | Yes                                                                                   |
| Brake                                    | No                                                                                    |
| Disc diameter (mm)                       | 125                                                                                   |
| Line lock out function                   | Yes                                                                                   |
| Max. cutting depth (mm)                  | 33                                                                                    |
| No load speed (rpm)                      | 2600 - 11,000                                                                         |
| Power input (W)                          | 1750                                                                                  |
| Sound power level (dB(A))                | 97.5                                                                                  |
| Sound power level uncertainty (dB(A))    | 3                                                                                     |
| Sound pressure level (dB(A))             | 86.5                                                                                  |
| Sound pressure level uncertainty (dB(A)) | 3                                                                                     |
| Spindle size                             | M 14                                                                                  |
| Standard equipment                       | Quick release safety guard, AVS side handle, FIXTEC flange nut, flange nut, 4 m cable |
| Supplied in                              | No kitbox or bag supplied                                                             |
| Switch type                              | Deadman switch                                                                        |
| Variable speed                           | Yes                                                                                   |
| Vibration grinding (m/s²)                | 9.4                                                                                   |
| Vibration grinding uncertainty (m/s²)    | 1.5                                                                                   |
| Vibration sanding (m/s²)                 | 3                                                                                     |
| Vibration sanding uncertainty (m/s²)     | 1.5                                                                                   |
| Weight (kg)                              | 2.8                                                                                   |