



47753555



IP55

SCHUKO socket outlet 2gang horizontal with hinged cover surface-mounted with labelling field, enhanced contact protection, Berker W.1

Technical features

Architecture

Design according to DIN 49440

Main electrical features

Nominal voltage	250 V
Rated current	16 A
Rated voltage	250 V AC

Cover, door

- with hinged cover that falls back, manual clip-in
- Complete housing

Materials

RAL colour	RAL 7011 - Iron grey
Colour of design line	grey/light grey
Colour	dark grey
Material	thermoplastic
Surface appearance	matt

Dimensions

Height	147 mm
Width	76 mm

Connection

Conductor cross-section	1 ... 2,5 mm ²
Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1
- with plug-in terminals	

Cable

- inserts wired-through
- with one entry for 2 cables and one entry for cable and tube

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Use

- with labelling field
- enhanced contact protection

Safety

Protection index IP	IP55
IK protection code against mechanical impacts	05
Enhanced contact protection (child protection)	according to IEC 60884-1
Enhanced contact protection (child protection)	according to VDE 0620-1
- Enhanced contact protection	

Use conditions

Operating temperature	-40 ... 30 °C
Storage/transport temperature	-50 ... 50 °C

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

- Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK