



Busch-Watchdog 220 MasterLINE KNX

Functions at a glance

- With 2 movement channels.
- With 1 twilight channel with 3 switching thresholds.
- No remote control possible via IR remote control KNX.
- With integrated KNX bus coupler.
- No additional power supply necessary.
- Surveillance density: 92 sectors with 368 switching segments.
- Twilight sensor: approx. 1 - 1000 lux
- Switch-off delay: approx. 10 sec to 1092 min
- Sensor angle: 220°
- Range: approx. 16 m
- Control element: 2 trim potentiometers
- Protection class (device): IP 55
- Temperature range (device): -25 °C - 55 °C
- Storage temperature range: -25 °C - 55 °C
- Transport temperature range: -25 °C - 70 °C
- Detection range: frontal: 16 m, lateral: 16 m
- Detection range 2:
- Brightness limit value: 1 Lux
- Detection angle: 220 °
- Dimensions: (L x W x D): 115 mm x 125 mm x 141 mm
- Mounting height: 2.5 m
- For software and description please check the current Online-Catalogue.
- Additional Power-Tool software necessary.

Order details

Article No.:	6179/01-204
Order No.:	2CKA006132A0311
EAN:	4011395168523
Customs tariff number:	85365080
Price group:	42
Price:	262,00 EUR plus VAT
Info sheet:	» Download PDF

Downloads

Instruction manual

- » [Installation and operating instructions](#)
- » [KNX updater tool - DE](#)
- » [Product manual](#)

Certificates

- » [EU-declaration of conformity](#)
- » [ROHS product declaration](#)

Software

- » [Additional software :PowerTool , V 1.2.122, 17.09.2019](#)
- » [ETS3 application , V 1.0, 01.02.2013](#)
- » [ETS4/ETS5 application , V 1.0, 01.02.2013](#)