




47501909



**SCHUKO socket outlet with labelling field, Berker S.1/B.3/B.7, polar white matt**

Technical features

**Architecture**

| | |
|---|---|
| Design | according to DIN 49440 |

**Main electrical features**

| | |
|---|---|
| Nominal voltage | 250 V |
| Rated current | 16 A |
| Rated voltage | 250 V AC |

**Cover, door**

- Central cover plate

**Materials**

| | |
|---|---|
| RAL colour | RAL 9010 - Pure white |
| Colour of design line | polar white |
| Colour | white |
| Colour | polarwhite |
| Material | thermoplastic |
| Surface appearance | matt |

**Dimensions**

| | |
|---|---|
| Insertion depth | 32 mm |

**Installation, mounting**

- with spreader claws

**Connection**

| | |
|---|---|
| Connection terminals | according to IEC 60884-1 |
| Connection terminals | according to VDE 0620-1 |

- with plug-in terminals

**Use**

- with labelling field

**Safety**

| | |
|---|---|
| Protection index IP | IP20 |
| IK protection code against mecanical impacts | 05 |

- without enhanced contact protection

**Identification**

| | |
|---|---|
| Main design line | Berker S.1/B.3/B.7 |
| Secondary design line(s) | Berker B.3, Berker S.1, Berker B.7 |

**Instructions**

- Labelling field height arranged for P-touch strips 6 mm.