

TR-002	
CPU	Micro processor with hardware RAID
Drive Bay	2 x 2.5-inch or 3.5-inch SATA 6Gb/s, 3Gb/s
Drive Compatibility	3.5-inch SATA 6Gb/s, 3Gb/s hard disk drives 2.5-inch SATA 6Gb/s, 3Gb/s hard disk drives 2.5-inch SATA 6Gb/s, 3Gb/s solid state drives
Hot-swappable	Yes
USB 3.0 port	1 x Type-C USB 3.1 Gen 2
Dimensions (HxWxD)	168.5, 102, 219
Weight (Net)	1.37
Max. number of HDDs/SSDs supported	2
Hard Drive Type	2 x 2.5-inch or 3.5-inch SATA 6Gb/s
Operating temperature	0 - 40 °C (32°F - 104°F)
Relative Humidity	5~95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	External Power Adapter, 36W, 100-240V
Power Consumption: HDD Sleep Mode	2.98
Power Consumption: Operating Mode, Typical	10.15
Fan	1 x 70mm, 12VDC
Sound Level	17.8
Kensington Security Slot	Yes

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.