

## LED-Licht in besonders flacher Bauform!

### Mobiler Slim LED-Strahler

#### Technische Highlights

- Für die Verwendung im Innen- und Außenbereich, IP54
- Extrem lange Lebensdauer der LEDs, stoßfest, wartungsfrei
- Minimale Wärmeentwicklung
- Hochwertiges, schwenkbares Metallgehäuse
- Standfestes Metallgestell mit Schaumstoffgriff
- Strahler stufenlos schwenk- und arretierbar
- Diese Leuchte enthält eingebaute LED-Lampen
- Die Lampen können in der Leuchte nicht ausgetauscht werden

#### Technische Daten

|                          |                             |
|--------------------------|-----------------------------|
| Versorgungsspannung:     | 230V, 50/60Hz               |
| Kabellänge:              | 5m                          |
| Kabelbezeichnung:        | H07RN-F 3G1.0               |
| Farbtemperatur:          | 6500K                       |
| Farbwiedergabeindex:     | 80                          |
| Schutzart:               | IP54                        |
| Lebensdauer LED:         | 50.000h                     |
| Abstrahlwinkel:          | 110°                        |
| Schwenkbereich vertikal: | 180°                        |
| Schutzklasse:            | I                           |
| Betriebstemperatur:      | -10°C ~ +40°C               |
| Farbe:                   | silber, Gestell melonengelb |



| Typenbezeichnung       | ML DN 2810 FL 5M DE<br>3925 | ML DN 5630 FL 5M DE<br>3925 | ML DN 9850 FL 5M DE<br>3925 |
|------------------------|-----------------------------|-----------------------------|-----------------------------|
| Art.-Nr.               | 1172900102                  | 1172900302                  | 1172900502                  |
| EAN                    | 4007123650231               | 4007123650248               | 4007123650255               |
| Leistung               | 10W                         | 30W                         | 50W                         |
| LEDs                   | 28 x 0,36W                  | 56 x 0,5W                   | 98 x 0,5 W                  |
| Lichtstrom             | 950lm                       | 2530lm                      | 4750lm                      |
| Wirkungsgrad Lampe     | 95 lm/W                     | 84 lm/W                     | 96 lm/W                     |
| gew. Energieverbrauch  | 9,9kWh / 1000h              | 30,2kWh / 1000h             | 49,2kWh / 1000h             |
| Energieeffizienzklasse | A+                          | A                           | A+                          |
| Maße                   | 19,8x20,9x14,4cm            | 26,1x28,9x16,4cm            | 30,0x33,9x18,9cm            |
| Gewicht                | 1,0kg                       | 1,7kg                       | 2,4kg                       |

#### Lieferumfang/ Art.-Nr./ EAN Nr.

- Im farbigen Verkaufskarton verpackt
- Art.-Nr./ EAN siehe oben
- VE: 1
- Lieferbar ab September 2017



## LED light in a particularly slim design!

### Mobile slim LED floodlight

#### Technical highlights

- For indoor and outdoor use, IP54
- Extremely long lifespan of the LEDs, impact resistant, maintenance-free
- Minimum heat development
- High-quality swivelling metal casing
- Stable metal framework with foam handle
- Floodlight steplessly pivotable and lockable
- This floodlight contains integrated LED lamps
- The lamps cannot be exchanged in floodlight

#### Technical data

|                         |                            |
|-------------------------|----------------------------|
| Supply voltage:         | 230V, 50/60Hz              |
| Cable length:           | 5m                         |
| Cable designation:      | H07RN-F 3G1.0              |
| Colour temperature:     | 6500K                      |
| Colour rendering index: | 80                         |
| IP class:               | IP54                       |
| Life cycle LED:         | 50,000h                    |
| Radiation angle:        | 110°                       |
| Swivel range, vertical: | 180°                       |
| Protection class:       | I                          |
| Operating temperature:  | -10°C ~ +40°C              |
| Colour:                 | silver, frame melon yellow |



| Type designation         | ML DN 2810 FL 5M DE 3925 | ML DN 5630 FL 5M DE 3925 | ML DN 9850 FL 5M DE 3925 |
|--------------------------|--------------------------|--------------------------|--------------------------|
| Art. no.                 | 1172900102               | 1172900302               | 1172900502               |
| EAN                      | 4007123650231            | 4007123650248            | 4007123650255            |
| Power                    | 10W                      | 30W                      | 50W                      |
| LEDs                     | 28 x 0.36W               | 56 x 0.5W                | 98 x 0.5 W               |
| Luminous flux            | 950lm                    | 2530lm                   | 4750lm                   |
| Efficiency, lamp         | 95 lm/W                  | 84 lm/W                  | 96 lm/W                  |
| total energy consumption | 9.9kWh / 1000h           | 30.2kWh / 1000h          | 49.2kWh / 1000h          |
| Energy efficiency class  | A+                       | A                        | A+                       |
| Dimensions               | 19.8x20.9x14.4cm         | 26.1x28.9x16.4cm         | 30.0x33.9x18.9cm         |
| Weight                   | 1.0kg                    | 1.7kg                    | 2.4kg                    |

#### Scope of delivery / art. No. / EAN no.

- Packed in a coloured sales cardboard box
- Art. no./ EAN see at top
- PU: 1
- Available from September 2017

