

Product datasheet

Specifications



APC Back-UPS Connect 12Vdc
36W, lithium-ion, mini network
ups to protect internet routers, IP
cameras and more

CP12036LI

Overview

Lead time Usually in Stock

Main

Main Input Voltage 12 V DC

Main Output Voltage 12 V DC

Battery type Li-Ion (Lithium-Ion)

Complementary

Number of tare power 2 W

Batteries & Runtime

Battery recharge time 9 h

Physical

Colour White

Width 99 mm

Depth 109 mm

Net weight 300 g

Mounting mode Not rack-mountable

Height 25 mm

Output

Output voltage 12 V

Conformance

Product certifications CE

Standards CE
EN/IEC 61000-4-8
EN/IEC 61000-4-2
EN/IEC 62368-1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-10...50 °C
Storage altitude	0...5000 m
IP degree of protection	< IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	11.6 cm
Package 1 Length	16.2 cm
Package 1 Weight	360 g
Unit Type of Package 2	BB1
Number of Units in Package 2	20
Package 2 Height	20 cm
Package 2 Width	39.5 cm
Package 2 Length	24.8 cm
Package 2 Weight	8 kg
Unit Type of Package 3	PAM
Number of Units in Package 3	960
Package 3 Height	92 cm
Package 3 Width	100 cm
Package 3 Length	120 cm
Package 3 Weight	411 kg
SCC14	10731304632396

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information

Contractual warranty

Warranty	24 months
----------	-----------

Recommended replacement(s)