ONKRON
designed to support

M6L-B





Screen size:
40" - 75"

Max load:
45.5 kg

VESA:
100x100 - 600x400 mm

Wall distance:
55 mm - 434 mm

Made of	Plastic, SPCC cold rolled steel
Max. load of monitors/TVs	45.5 kg
VESA	100x100, 100x200, 200x100, 200x200, 200x300, 200x400, 300x100, 300x200, 300x300, 300x400, 400x200, 400x300, 400x400, 500x200, 500x300, 500x400, 600x200, 600x300, 600x400 mm
Screen size (min)	40"
Screen size (max)	75"
Wall distance (min)	55 mm
Wall distance (max)	434 mm
Upward tilt angle (max)	4°
Downward tilt angle (max)	4°
Angle of rotation (range)	8°
Warranty	5 years
Overall dimensions complete	64.4x50x43 cm
Dimensions of the individual package	45x23.4x6.5 cm
Overall dimensions of the group pack	46,5 x 24,9 x 22,5 cm
Individual package volume	6.84 m³
Gross weight individual	5.2 kg
Group gross weight	15.65 kg
Number in group	3 item(s)

ONKRON mounting solutions:
· Are suitable for continuous 24/7 use when installed and used in accordance with the applicable product documentation, installation instructions, and load specifications;
· Are intended for professional and commercial installations;
· Are designed to support secure and reliable installation of compatible displays in public environments;
· Comply with standard safety, installation, and mechanical requirements applicable to professional display mounting solutions;
· May be used in high-traffic public spaces, provided that installation is performed by qualified personnel and in accordance with all applicable local regulations, safety standards, and project requirements.

© 2026 Products or images of ONKRON™ are subject to change without notice.