



## UNYSAT 24TN-LNB

SCR-LNB for 24 participants

EAN	Item no.	Box	Device (W x H x D)	Weight	Weight (Box)	Colour
4019588088245	0000/8824	21.00 x 20.50 x 19.50 cm	20.00 x 19.00 x 19.50 cm	440 g	500 g	grey

### ENVIRONMENT

Humidity: 10 ... 90 %

Ambient temperature: -30 ... 60 °C

### GENERAL CHARACTERISTICS

Top features: 24 participants on a cable

Top features: SCR protocol according to EN 50494 & EN50607

Top features: Participants 1-8 works with EN 50494 or EN50607

Top features: From participant 9 only support of EN50607

Top features: Suitable for mounting on all SATMAN dish

Top features: Antenna mode for easy alignment of the antenna

### INPUT FREQUENCY RANGE

Frequency range: 10.7 ... 12.75 GHz

### LOF

Lower frequency range: 10.4 GHz

Upper frequency range: 10.4 GHz

### NOISE FACTOR

Noise figure: 1 dB

### OUTPUT FREQUENCY RANGE

Frequency range: 950 ... 2150 MHz

### POWER SUPPLY

Power consumption: max. 350 mA @13,5 V

### SINGLE-CABLE OUTPUT

Output frequency: 950 ... 2150 MHz

Number of output channels: 24

Frequency of the output channels: 975, 1025, 1075, 1125, 1175, 1225, 1275, 1325, 1375, 1425, 1475, 1525, 1575, 1625, 1675, 1725, 1775, 1825, 1875, 1925, 1975, 2025 MHz

### TECHNICAL DATA

Outputs: 1

Feed reception: Für SATMAN

### SCOPE OF DELIVERY

TechniSat SCR-LNB