

# T2250

At home in  
all applications



#### HIGHLIGHTS AT A GLANCE:

- Multifunctional dot matrix printer for a wide variety of applications
- Flexible paper input via cut sheet feeders and endless tractors
- Extensive automatic functions for unattended printing
- Diversity of interfaces, emulations and drivers
- Robust construction for reliable and quiet operation



# T2250

With the T2250 DASCUM provides a dot matrix printer, which is characterized by a particularly extensive equipment. Print speed and monthly print volume, ease-of-use and reliability - the T2250 with 136-character print width offers an excellent price / performance ratio.

Extensive automatic functions such as paper thickness scanning, paper path switching and single sheet feed detection as well as numerous standard and optional paper processing functions ensure optimum readiness of the printer in a wide variety of application areas.

## TECHNICAL DATA

<b>Print Speed</b>	720 cps (Fastest Draft), 600 cps (Draft), 270 cps (DPQ), 180 cps (NLQ) bei 10 cpi
<b>Resolution</b>	up to 360 x 360 dpi
<b>Throughput</b> (ECMA 132)	482 pages per hour
<b>Character Density</b>	10, 12, 15, 17.1, 20 cpi
<b>Line Density</b>	2, 3, 4, 6, 8, 12 lpi
<b>Lifetime Print Head</b>	400 million characters
<b>Memory</b>	128 kB
<b>Interfaces</b>	Parallel (bi-directional) and Serial RS232
<b>Emulation Standard</b>	IBM ProPrinter XL24, Epson LQ2250, MTPL + Barcode + LCP IGP Version: IGP/PGL, Code V, MT660, Printronix P6000, HP2564C, Genicom ANSI
<b>Emulation Optional</b>	DEC LA 75, ECMA 9011, Eastern Europe, MT50
<b>Fonts</b>	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 barcodes and large characters printing
<b>Consumables</b>	Ribbon: 5 million characters
<b>Paper Handling Standard</b>	Push tractor and friction, Continuous aper with straight paper path, Manual cut sheet from front, tear-off function, park position
<b>Paper Handling Optional</b>	Additional push tractor front, additional push tractor rear
<b>Copies</b>	Push tractor front: 1 original + 5 copies; Push tractor rear: 1 original +1 copies; Cut sheet: 1 original + 5copies
<b>Paper Types</b>	Continuous paper, single sheet, multi-part forms
<b>Paper Weight</b>	60-120 g/m <sup>2</sup>
<b>Paper Format</b>	Width: 76 to 420 mm; Length: 76 to 599 mm
<b>Weight</b>	10,5 kg
<b>Dimension</b>	600 x 300 x 295 mm (W x D x H)
<b>Noise Level</b>	53 dB(A)
<b>Voltage</b>	230 V - 50/60 Hz
<b>Power Consumption</b>	40 Watt (Printing); <10 W (Sleep Mode)
<b>Temperature</b>	+10° to +35° C; 20% to 80% rel. humidity
<b>Print Volume</b>	26.000 pages per month
<b>MTBF</b>	20.000 hours
<b>Driver</b>	Windows 7/8/10 and Server 2008/2012 (32/64 Bit); SAP

### Configurations:

- **T2250** Standard model

#### DASCUM GB Ltd

Hart House, Priestley Road  
Basingstoke | Hampshire RG24 9PU | ENGLAND  
Tel.: +44 1256 355 130 | Fax: +44 1256 481 400  
info.gb@dascom-com | www.dascom.co.uk

#### DASCUM Europe GmbH

Heuweg 3 | 89079 Ulm | GERMANY  
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100  
info@dascom.com | www.dascomeurope.de

#### DASCUM (Holdings) LTD.

R. 1811-1816A | Nan Fung Centre  
264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong  
Tel.: +852 2498 1507 | Fax: +852 2413 6047