


2U 8-bay 2.5" / 3.5" HDD / SSD rackmount storage chassis with Mini-SAS HD SFF-8643 12Gb/s interface

RM22-308



- Backplane support for 8 port SAS / SATA drives and 12Gb/s Mini-SAS HD SFF-8643 + SGPIO
- Supports eight 2.5"/3.5" SAS/SATA HDD/SSD hot-swap trays
- Includes three 80mm x 38mm hot-swappable PWM fans
- Independent drive status LED
- Supports E-ATX or SSI-EEB motherboards
- Supports seven low profile PCI / PCIe slots
- Auto lock handle designed to easily fit and secure into server racks

Specifications

Model No.	SST-RM22-308
Chassis form factor	2U
Motherboard	SSI-EEB, SSI-CEB, Extended ATX, ATX, Micro-ATX, Mini-ITX
Drive Bay	External 3.5" hot-swap x 8 Internal 2.5" x 2 (up to 15mm), slim optical x 1 (up to 12.7mm)
Power Supply	2U single or 2U redundant (not included) ***
Limitation of CPU cooler	68mm
Power connector on HDD backplane	4-Pin peripheral x 2
Cooling System	Hot-swap 80 x 38mm PWM fan x 3
Expansion Slot	Low profile PCI / PCIe x 7
Front I/O Port	USB 2.0 x 1, USB 3.1 Gen 1 Type-A x 1 **
Front buttons	Power On / Off, system reset
LED Indicator	Chassis Power LED x 1: Blue HDD Access x 1: Green LAN LED x 2: Green HDD Tray HDD Power LED x 8: Yellow HDD Access x 8: Blinking green
HDD backplane	8 ports SAS / SATA to Mini-SAS HD SFF-8643 x 2 with SGPIO
HDD Interface	SAS III / II / I, SATA III / II / I
Main metal thickness	1.2mm
Net weight	10.1kg
Dimension	430mm (W) x 88.5mm (H) x 660mm (D), 25.1Liters 16.93" (W) x 3.48" (H) x 26" (D), 25.1Liters

* Compatible with tool-less rail slide - RMS03-26

**RM22's USB internal cable is 800mm long, so if you are connecting an external enclosure to the USB3.1 port, we recommend using it with shorter cables to prevent performance loss.

***Please make sure the mounting holes of your 2U PSU matches the mounting holes on the rear panel of RM22-308 (Please refer to RM22-308's official product webpage)



SILVERSTONE



Distinctive exterior

Distinctive front panel features 8 x hot-swappable 3.5" bays, 1 x slim ODD bay along with handle bars allowing for easy accessibility to the internal components.



3.5" x8



2.5" x2



Cooling capabilities

Utilizing the typical front-to-back directional airflow, RM22-308 comes pre-installed with three 80mm x 38mm hot-swappable PWM fans, designed to achieve a rapid heat dissipation effect that does not easily accumulate hot air inside.



Internal configurations



SSI-EEB, SSI-CEB, Extended ATX, ATX, Micro-ATX, Mini-ITX



CPU cooler height limitation: 68mm



2U single or 2U redundant

Sliding rail compatibility

Reserved mounting holes for sliding rails which can be easily installed. Can be used with RMS03-26 rail.

