

LUX: Light Up Your Vision

- Mini-Format, Max-Power: 60 W Lichtleistung im handlichen Cube-Format
- RGB & Bi-Color: 360 RGB-Farben + 2.700–6.500 K für höchste Flexibilität
- Smarte Steuerung: Direkt am Gerät oder per App – schnell und intuitiv
- Zwei Lade-Optionen: USB-C PD & DC-In für maximale Flexibilität
- Kreative Lichteffekte: 13 FX-Modi für dynamische Szenen und starke Looks



Technische Daten

Anzahl LEDs	1
Leistung	60,0 W
Farbtemperatur	2.700 – 6.500 K
Farben	0 – 359° (HSI-Modus), Sättigung 0-100%
Farbwiedergabeindex (CRI) Television Lighting Consistency Index (TLCI) TN-30-18	96+ 95+ Rf 95 / Rg 96
Leistungsregelung	0 – 100 %, in 1-%-Schritten
Beleuchtungsstärke (ohne Reflektor)	2.700 K: 7.070 lx (0,5 m), 1.690 lx (1 m), 806 lx (1,5 m) 4.300 K: 7.980 lx (0,5 m), 2.040 lx (1 m), 953 lx (1,5 m) 5.600 K: 7.990 lx (0,5 m), 2.100 lx (1 m), 981 lx (1,5 m) 6.500 K: 7.980 lx (0,5 m), 2.170 lx (1 m), 947 lx (1,5 m)
Beleuchtungsstärke (mit Reflektor)	2.700 K: 32.000 lx (0,5 m), 7.980 lx (1 m), 3.620 lx (1,5 m) 4.300 K: 28.800 lx (0,5 m), 7.140 lx (1 m), 3.100 lx (1,5 m) 5.600 K: 26.000 lx (0,5 m), 6.400 lx (1 m), 2.820 lx (1,5 m) 6.500 K: 24.500 lx (0,5 m), 5.670 lx (1 m), 2.550 lx (1,5 m)
Beleuchtungswinkel COB-Dauerlicht	120 °
Flicker-frei	> 240 fps
Effekte	13
Bowens S-Type-Bajonett	Nein
Fernsteuerung	App
Frequenzband	2,402 – 2,480 GHz
Maximal abgestrahlte Sendeleistung	10 dBm
Stromversorgung	Lithium-Ionen-Akku (14,8 V / 4000 mAh / 59 Wh)
Akkulaufzeit	59 min (100 % Helligkeit), 2 h (50 % Helligkeit), 10 h (10 % Helligkeit)
Ladezeit Akku	1h 48 min (100 %)
Eingang	DC 2,5: 16,8 V 4,44 A max. 20,0 V / 3,73 A max. USB-C: 20,0 V / 2,0 max.
Nenn-Eingangsleistung	60,0 Watt
Lautstärke Lüftung	28 dB (100 % Helligkeit, 1 m)
Anschlüsse	Stromanschluss, Stativ-Halterung, LUX-Mount
Material	ABS-Kunststoff
Betriebstemperatur	-10° – 40°
Maße (L x B x H) Gewicht (COB-Dauerlicht)	9,6 x 9,6 x 12 cm 911 g

Lieferumfang

Lieferumfang	1x COB-Lampe, 1x Schutzkappe, 1x 60W USB-C-Kabel, 1x Boost-Reflektor, 1x Cold-Shoe-Adapter 1x Bedienungsanleitung
Verpackungsmaße (L x B x H) Gewicht	29 x 16,1 x 11,8 cm 960 g

Änderungen von Design und technischen Daten bleiben vorbehalten und bedürfen keiner Ankündigung.

ArtikelNr.: 28448

LUX: Light Up Your Vision

- Mini format, max power: 60 W light output in a handy cube format
- RGB & Bi-Color: 360 RGB colors + 2,700–6,500 K for maximum flexibility
- Smart control: Directly on the device or via app – fast and intuitive
- Two charging options: USB-C PD & DC-In for maximum flexibility
- Creative lighting effects: 13 FX modes for dynamic scenes and strong looks



Technical Data

Number of LEDs	1
Power	60.0 W
Color temperature	2.700 – 6.500 K
Hues	0 – 359°(HSI Mode), Saturation 0-100%
Color rendering index (CRI) Television Lighting Consistency Index (TLCI)	96+ 95+ Rf 95 / Rg 96
Power adjustment	0 – 100 %, in 1-%-steps / in 10-%-steps
Illuminance (without reflector)	2,700 K: 7,070 lx (0.5 m), 1,690 lx (1 m), 806 lx (1.5 m) 4,300 K: 7,980 lx (0.5 m), 2,040 lx (1 m), 953 lx (1.5 m) 5,600 K: 7,990 lx (0.5 m), 2,100 lx (1 m), 981 lx (1.5 m) 6,500 K: 7,980 lx (0.5 m), 2,170 lx (1 m), 947 lx (1.5 m)
Illuminance (with reflector)	2,700 K: 32,000 lx (0.5 m), 7,980 lx (1 m), 3,620 lx (1.5 m) 4,300 K: 28,800 lx (0.5 m), 7,140 lx (1 m), 3,100 lx (1.5 m) 5,600 K: 26,000 lx (0.5 m), 6,400 lx (1 m), 2,820 lx (1.5 m) 6,500 K: 24,500 lx (0.5 m), 5,670 lx (1 m), 2,550 lx (1.5 m)
Illumination angle COB continuous light	120°
Flicker free	240 fps
Light effects	13
Bowens S-type mount	No
Remote control	App
Radio frequency band	2.402 – 2.480 GHz
Transmission power maximum	10 dBm
Power supply	Lithium-ion battery (14.8 V / 4000 mAh / 59 Wh)
Battery running time	59 min (100% brightness), 2 h (50% brightness), 10 h (10% brightness)
Charging time battery	1h 48 min (100 %)
Input	DC 2.5: 16.8 V 4.44 A max. 20.0 V / 3.73 A max. USB-C: 20.0 V / 2.0 max.
Rated input power	60.0 W
Volume cooling fan	28 dB (100 % brightness, 1 m)
Connections	Power connection, tripod mount, LUX mount
Operating temperature	-10° – 40°
Material	ABS plastic
Dimensions (L x W x H) Weight	9.6 x 9.6 x 12 cm 911 g

What's in the Box and Packaging Details

What's in the box	1x COB light, 1x protective cap, 1x 60W USB-C cable, 1x Boost reflector, Cold-Shoe-Adapter, 1x manual
Packaging dimensions (L x W x H) Weight	29 x 16.1 x 11.8 cm 960 g

Specifications are subject to change without notice.

