

ASUS TUF Gaming VG27AQ



Highlights

EAN:
4718017296762
Produkt Nummer:
90LM0500-B01370

Spezifikationen

Display	Panel Size: Wide Screen 27.0"(68.47cm) 16:9 Color Saturation : 99%(sRGB) Panel Type : IPS True Resolution : 2560x1440 Display Viewing Area(HxV) : 596.74 x 335.66 mm Display Surface : Non-glare Pixel Pitch : 0.233 mm Brightness(Max) : 350 cd/? Contrast Ratio (Max) : 1000:1 Viewing Angle (CR?10) : 178°(H)/178°(V) Response Time : 1ms MPRT* Display Colors : 16.7M Flicker free HDR (High Dynamic Range) Support : Yes (HDR-10) Refresh Rate(max) : 155Hz
Video Feature	Trace Free Technology : Yes Color Temperature Selection : 4 Modes GamePlus(modes) : Yes (Crosshair/Timer/FPS Counter/Display Alignment/Sniper) Low Blue Light : Yes HDCP support : Yes GameVisual :7 Modes(Scenery/Racing/Cinema/RTS/RPG/FPS/sRGB Modes/MOBA Mode) G-Sync compatible Adaptive-Sync supported :Yes GameFast Input technology Multiple HDR Mode : Yes Shadow Boost ELMB SYNC
Audio Features	Stereo Speakers : 2W x 2 Stereo RMS
I/O Ports	Signal Input : HDMI(v2.0) x2, DisplayPort 1.2
Signal Frequency	Digital Signal Frequency : DisplayPort?30 ~243 KHz (H) /48 ~155 Hz(V) HDMI : 30 ~230 KHz (H) /48 ~144 Hz(V)
Power Consumption	Power Consumption Power Saving Mode Power Off Mode
Mechanical Design	Chassis Colors : Black Tilt : +33°--5° Swivel : +90°--90° Pivot : +90°--90° Height Adjustment : 0~130 mm VESA Wall Mounting : 100x100mm
Security	Kensington lock
Dimensions	Phys. Dimension with Stand(WxHxD) : 620x(377~507)x211mm Phys. Dimension without Stand (WxHxD) : 620x363x66mm Box Dimension(WxHxD) : 704x464x210mm

Weight	Net Weight (Esti.) : 5.8 kg Weight without stand : 3.5 kg Gross Weight (Esti.) : 8.0 kg
---------------	---

Accessories	Power cord Power adapter DisplayPort cable (Optional) Quick start guide HDMI cable (Optional) Warranty Card
--------------------	--

Compliance and Standards	BSMI, CB, CCC, CE, CEL level , CU, ErP, FCC, J-MOSS, KCC, PSE, RoHS, UkrSEPRO, UL/cUL, VCCI, WEEE, WHQL (Windows 10, Windows 8.1, Windows 7), MEPS, RCM, TUV Flicker-free , eStandby, TUV Low Blue Light, ICES-3, PC recycle
---------------------------------	--

Note	*1ms MPRT spec is based on internal testes. Response time may vary depending on test conditions **measuring a screen brightness of 200 nits without audio/ USB/ Card reader connection ***Adaptive-Sync (G-Sync compatible) technology supported (48Hz-155Hz)
-------------	---
