

GEP-1621 Version: 1



16-Port-Gigabit-PoE-Switch, 802.3af/at PoE

The LevelOne GEP-1621 is a Gigabit PoE-Plus Switch with 16 x 10/100/1000Base-T PoE-Plus ports. This switch is IEEE 802.3af/at compliant, providing power and data over a single Ethernet cable to any PoE device, with total power budget of 240W, up to 30W per port. Ideal for desktops, it is also 19-inch rack-mountable, which provides convenient and flexible installation. The GEP-1621 is designed for small-to-median businesses that prefers an affordable solution for PoE deploying infrastructure.



1. LED Indicators
2. 10/100/1000Mbps RJ-45 PoE Ports
3. Power Socket
4. Power Switch

Key-features

- 16 PoE-Plus Gigabit Ethernet Ports
- 10/100/1000Mbps Übertragungsgeschwindigkeit
- IEEE-802.3af / at PoE kompatibel zur einfachen Verwendung und Installation
- Automatische Erkennung und Schutz von Nicht-Standard-PoE-Geräten
- 9K Jumbo-Frames für hohe Transferraten
- Unterstützt Auto-Learning und Auto-Aging für bis zu 8K MAC-Adressen
- IEEE-802.3x Flow-Control schützt vor Packet-Loss und sorgt für zuverlässige Datenübertragung
- Minimiert den Stromverbrauch durch moderne Energieeffizienz (IEEE-802.3az)
- 19" Metallgehäuse
-



Related Product



POR-1220

Gigabit Outdoor PoE Repeater, Kaskadier, 802.3af/at PoE

Specifications

System Specifications

Standards & Protokolle:

IEEE 802.3 10-BASE-T, Ethernet
IEEE 802.3u 100-BASE-TX, Fast Ethernet
IEEE 802.3ab 1000BASE-T, Gigabit Ethernet
IEEE 802.3x Flow Control (full-duplex flow control)
IEEE 802.3af Power over Ethernet (PoE)
IEEE 802.3at Power over Ethernet Plus (PoE+)
IEEE 802.3az Energy-Efficient Ethernet

Pufferspeicher:

256KB

Stecker und Verkabelung:

16 x RJ-45 10/100/1000Base-T PoE-Plus ports

Indikator:

Power; Link/Active; PoE

Übertragungsmethode:

Store-and-Forward

Leistungsaufnahme:

100-240V AC, 50-60 Hz, Internal Power Supply

Energieverbrauch:

< 120W (GEP-1621W120)
< 150W (GEP-1621W150)
< 250W (GEP-1621)
< 380W (GEP-1621W380)

Features

Allgemein:

Flow Control: Half Duplex - Backpressure; Full Duplex - Pause frame

PoE:

Power Budget: Max. 110W (GEP-1621W120)

Max. 140W (GEP-1621W150)

Max. 240W (GEP-1621)

Max. 370W (GEP-1621W380)

Power Output: Up to 30W per port

Protection: Circuit protection to prevent power interference between ports

Pin Assignment: 1/2(+), 3/6(-)

Performance

Backplane (Gbps):

32Gbps

MAC-Adresstabelle:

8K

Datenrate:

10/100/1000Mbps

Weiterleitungsrate:

1000Mbps port - 1,488,000pps

100Mbps port - 148,000pps

10Mbps port - 14,880pps

Jumbo-Frames:

9KB

Environment

Energieeffizienz:

IEEE 802.3az Energy Efficient Ethernet:

- Automatically turns power off on RJ-45 port when detecting link down or Idle of client
- Cable length detection: Adjusts the signal strength based on the cable length
- Reduces the power consumption for cables shorter

Temperatur (°C):

Operating: 0°C ~ 50°C

Storage: -40°C ~ 70°C

Luftfeuchtigkeit (nicht kondensierend):

Storage: 5% ~ 90%

Operating: 5% ~ 90%

Einsatz:

19-inch rack-mountable

Physical Specifications

Abmessungen (W x D x H mm):

480 x 200 x 44 mm

Gewicht:

2900g

Zuverlässigkeit

MTBF:

48300 hours


Approval and Compliance

Zertifizierung:

FCC Part 15 Class A, CE, RoHS



Diagramm



Order Information

GEP-1621: 250W

GEP-1621W380: 380W

GEP-1621W150: 150W

GEP-1621W120: 120W

Package Contents

GEP-1621

Stromkabel

Quick Installation Guide

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.