

Surfaces: **brushed redgold** Art. no. : **35309310**



- Shower head size: 250 x 250 mm
- Spray pattern: PowderRain
- dynamic spray nozzles move out while using
- Spray face: metal
- maximum flow rate 18.1 l/min at 3 bar
- Flow rate PowderRain (at 3 bar): 18.1 l/min at 3 bar
- Operating pressure: min. 1,8 bar/max. 6 bar
- overhead shower removable for cleaning
- Installation: ceiling mounted

£ 1,608.88

Quick Clean



reddot winner 2020

red**dot** winner 2021

A large grid of small circles, with the word 'AXOR' centered in the middle. The circles are arranged in a regular pattern, and the word 'AXOR' is printed in a bold, sans-serif font in the center of the grid.

Technical drawing of the 3000 series terminal block showing front and top views with dimensions.

Front View Dimensions:

- Overall width: 145
- Overall height: 71
- Mounting flange height: 25
- Terminal block height: 56


Top View Dimensions:

- Overall width: 238
- Overall height: 238
- Internal width: 106
- Internal height: 145
- Mounting hole diameter: $G1/2$
- Terminal hole diameter: $G1/2$
- Terminal pitch: 22
- Mounting flange thickness: 53
- Mounting flange offset: 50

AXOR ShowerSolutions
Overhead shower 250/250 1jet ceiling
 Surfaces: **brushed redgold** Art. no. : **35309310**



Flowchart



The consumption was measured in combination with the appropriate fittings (thermostat/mixer/in-wall valve) to reflect actual application in practice.


AXOR ShowerSolutions

Overhead shower 250/250 1jet ceiling


Surfaces: **brushed redgold** Art. no. : **35309310**



Installation examples



AXOR 250 1jet
35287000
AXOR 300 1jet
35302000



AXOR 250/250 1jet
35309000
AXOR 300/300 1jet
35317000

