



16406094



Relay switch with centre plate for hotel card Berker Q.1/Q.3/Q.7/Q.9

Technical features

Main electrical features

Nominal voltage	230 V
Rated voltage	230 V AC

Electric current

Inductive load at $\cos \varphi = 0.6$	max. 6 A
--	----------

Power

Power consumption	< 0.2 W
Conventional transformers	1500 VA
Electronic transformers	1500 W

Materials

RAL colour	RAL 9006 - White aluminium
Colour of design line	aluminium
Colour	aluminium optics
Colour	aluminium
Material / workmanship	lacquered
Material	Plastic/metal
Surface appearance	velvety

Dimensions

Depth	57,3 mm
Insertion depth	32 mm
Height	71 mm
Width	71 mm
Card thickness	0,8 ... 1,2 mm
Card width	max. 55 mm

Fluorescent bulbs control

Compact fluorescent lamps	500 W
Fluorescent lamps in duo circuit	1500 W

LED control

- illuminated with blue LED if hotel card is not inserted

Incandescent bulbs control

230 V incandescent lamps and halogen lamps	1500 W
--	--------

Installation, mounting

- with spreader claws

Connection

Screw terminals (max.)	2 x 2,5 mm ²
- with screw-in lift terminals	

Settings

Delay time incrementally adjustable	0, 15, 30, 60 s
- with potentiometer for incremental adjustment of delay time	

Equipment

- for illumination
- with potential-free contact

Safety

Protection index IP	IP20
---------------------	------

Use conditions

Operating temperature	-5 ... 50 °C
Storage/transport temperature	-25 ... 70 °C (storage at > 45°C reduces the service life)

Identification

Application, usage	Light control
Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.3, Berker Q.1