

AV PRO microSD



microSDXC UHS-II V60 A1

M M C R O



ANGELBIRD.COM


PROFESSIONAL PERFORMANCE
microSD™ FOR RECORDING 4K
AND BEYOND.



OUR AV PRO microSD CARDS OFFER PROFESSIONAL GRADE TECHNOLOGY WITH EXTREME DURABILITY FOR ALL ELEMENTS OF LAND, SEA AND AIR. WITH LARGE CAPACITY OPTIONS AVAILABLE, THESE CARDS ARE IDEAL FOR 4K+ DRONES, ACTION CAM POV RECORDING, CAMERA SYSTEMS AND GAME CONSOLES.

AV PRO
microSD

SPECIFICATIONS AND FEATURES

	Speeds¹	READ	WRITE
	SEQUENTIAL	280 MB/s	160 MB/s
	SUSTAINED	260 MB/s	140 MB/s



Tested and Approved Sustained Performance for RAW up to 6K Production



128 GB | 256 GB



Stable Stream™ Maintains Performance for the Capacity of the Card



microSDXC™ | UHS-II | U3 Class 10 | V60 | A1



X-Ray & Magnetic Proof



Shock, Dust, Water & Temperature Proof



microSD-to-SD UHS-II Adapter Included



Operation: -25 °C | 85 °C
Storage: -40 °C | 85 °C



Sticker-Free™

MEMORY CARDS

Specifications are subject to change without notice.
Specifications are provided "as is" without warranty of any kind.
202008041618

SPECIFICATIONS / ORDERING

AVP
RO
microSD

GENERAL SPECIFICATIONS

Capacity
128 GB | 256 GB

Dimensions
11.0 × 15.0 × 0.7 mm
(0.43 × 0.59 × 0.03 in)

Form Factor
microSD

Weight
~ 0.25 g (excl. adapter)

TECHNICAL SPECIFICATIONS

Interface
SDXC™, SD 6.1, UHS-II

Features
Wear leveling, power management for low power usage, ECC, water resistant

PERFORMANCE SPECIFICATIONS

Sequential Speed¹
Read up to 280 MB/s
Write up to 160 MB/s

Sustained Speed¹
Read up to 260 MB/s
Write up to 140 MB/s

RELIABILITY SPECIFICATIONS

Data Reliability
ECC function

Certifications
RoHS, CE, FCC

ELECTRICAL SPECIFICATIONS

DC input voltage
1.8 V ± 5 %

Power usage (idle/max)
2 mW / 1.2 W

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature
-25 °C | 85 °C

Storage Temperature
-40 °C | 85 °C

Operating Humidity
25 % to 85 % non-condensing

WARRANTY³

3-year limited warranty

PACKAGE CONTENT

- AV PRO microSD V60
- microSD-to-SD UHS-II Adapter
- Activation code for full limited warranty



RETAIL PACKAGING DETAILS


Box dimension
125.0 × 115.0 × 23.0 mm
(4.92 × 4.53 × 0.91 in)

Weight
~ 37.0 g | ~1.3 oz

- ¹ Speed based on internal testing. Actual transfer rates and capacity may vary depending on the product model, system hardware and other factors.
- ² 4K, 6K and Full HD support may vary depending on host device, file attributes, and other factors.
- ³ To receive the full limited warranty, the product needs to be registered on the Angelbird Personal Service Portal within 30 days after purchase. If not registered within this period, the market-specific legal guarantee period comes into force.

This device complies with Part 15 of the FCC Rules. SD™, SDXC™ and microSD™ are trademarks of SD-3C LLC.

Other product names used herein are for identification purposes only and may be trademarks of their respective owners. Angelbird disclaims any and all rights in those marks.



ORDERING INFORMATION

Capacity	SKU	EAN	UPC
● 128 GB	AVP128MSDV60	9120056585380	812937024208
● 2× 128 GB	AVP128MSDV60X2	9120056585397	812937024215
● 256 GB	AVP256MSDV60	9120056585403	812937024222
● 2× 256 GB	AVP256MSDV60X2	9120056585410	812937024239

MEMORY CARDS

Specifications are subject to change without notice. Specifications are provided "as is" without warranty of any kind.

202008041618