

MASTERLIQUID ATMOS II Stealth Series



Experience ultimate thermal management with the MasterLiquid Atmos II Stealth. This refined cooling solution features a 29mm thickened radiator for superior heat dissipation and pressure-optimized Mobius 120P fans for silent, high-performance airflow. A sleek, ultra-low-profile pump ensures maximum case compatibility, while the magnetic Flex Kit allows for effortless customization with interchangeable covers. Complete with a universal quick-mount kit and pre-installed fans, the Atmos II Stealth blends sophisticated aesthetics with a streamlined installation process.

FEATURES

BUNDLED FLEX KIT FOR MODULAR UPGRADES

Interchangeable magnetic top covers offer versatile customization and effortless swapping. This kit includes base, metallic, and VRM fan options to meet diverse aesthetic and thermal requirements with ease.

MOBIUS 120P FANS

Pressure-optimized fans featuring loop dynamic bearings ensure silent, high-performance airflow even under heavy loads.

THICKER RADIATOR FOR BETTER PERFORMANCE

An increased radiator thickness—upgraded from 27mm to 29mm—enlarges the heat exchange surface for more efficient heat absorption and dissipation. This enhancement maintains thermal stability during demanding workloads, ensuring reliable cooling when the system reaches peak limits.

ULTRA-LOW PROFILE PUMP DESIGN

The sleek, flat design ensures compatibility with various case sizes while delivering high-performance liquid flow.

EASY INSTALLATION

A quick-mount kit provides broad compatibility with mainstream processor sockets, while pre-installed fans simplify the setup process.

Default Cover



Metallic Finish Cover



VRM Fan



FLEX-KIT

INSTANT SWITCH SOLUTION

With magnetic mounting, users can seamlessly swap the pump cover.

MODULAR OPTIONS – METALLIC FINISH COVER

The metallic finish cover provides a minimalist, high-end aesthetic with a sleek, reflective surface.

MODULAR OPTIONS – BLACK BASE COVER

The standard matte black plate serves as the core foundation for a clean, understated build.

MODULAR OPTIONS – VRM FAN

The VRM fan module cools the motherboard's hot zones with airflow in six directions. It can reduce temperatures by up to 13°C*, improving both stability and performance.

*Tested by Cooler Master Lab.



MASTERLIQUID ATMOS II STEALTH SPECIFICATIONS

Model Name	MasterLiquid Atmos II Stealth 240	
Model Number	MLX-D24M-A24DK-R1	
CPU Socket Support	Intel	Intel® LGA 1851 / 1700 / 1200 / 1150 / 1151 / 1155 / 1156
	AMD	AMD® AM5 / AM4
Waterblock Dimensions	92.5 x 87 x 39 mm (3.6 x 3.4 x 1.5 inch)	
Radiator	Material	Aluminum
	Dimension (LxWxH)	277 x 119.2 x 29 mm (10.9 x 4.7 x 1.1 inch)
Tube	Length	350 mm
Pump	Noise Level (Max)	25 dB(A)
	Profiles	Non-LED
	Speed	3400 ± 300 RPM
	MTTF	> 210,000 hours
	Rated Voltage	12 VDC
	Power Consumption	3.84 W
	Connector	4 Pin PWM
Flex-Kit	Model Name	VRM Fan
	Exterior Color	Black
	Dimensions	85.0 x 78.5 x 25.5 mm (3.4 x 3.1 x 1 inch)
	Profiles	NON LED
	Quantity (pcs)	1 PCS
	Wire Length	1000 mm
	Speed	690 ~ 4000 ± 10% RPM
	Air Flow (Max)	15.8 m³/h (9.3 CFM)
	Air Pressure (Max)	2.8 mmH₂O
	Noise Level (Max)	36 dB(A)
	MTTF	> 50,000 hours
	Bearing	Loop dynamic bearing
	Connector	4-Pin PWM
	Rated Voltage	12 VDC
	Rated Current	0.15 A
	Safety Current	0.25 A
	Power Consumption	1.8 W

Model Name	MasterLiquid Atmos II Stealth 360	
Model Number	MLX-D36M-A24DK-R1	
CPU Socket Support	Intel	Intel® LGA 1851 / 1700 / 1200 / 1150 / 1151 / 1155 / 1156
	AMD	AMD® AM5 / AM4
Waterblock Dimensions	92.5 x 87 x 39 mm (3.6 x 3.4 x 1.5 inch)	
Radiator	Material	Aluminum
	Dimension (LxWxH)	394 x 119.2 x 29 mm (15.5 x 4.7 x 1.1 inch)
Tube	Length	400 mm
Pump	Noise Level (Max)	25 dB(A)
	Profiles	Non-LED
	Speed	3400 ± 300 RPM
	MTTF	> 210,000 hours
	Rated Voltage	12 VDC
	Power Consumption	3.84 W
	Connector	4 Pin PWM
Flex-Kit	Model Name	VRM Fan
	Exterior Color	Black
	Dimensions	85.0 x 78.5 x 25.5 mm (3.4 x 3.1 x 1 inch)
	Profiles	NON LED
	Quantity (pcs)	1 PCS
	Wire Length	1000 mm
	Speed	690 ~ 4000 ± 10% RPM
	Air Flow (Max)	15.8 m³/h (9.3 CFM)
	Air Pressure (Max)	2.8 mmH₂O
	Noise Level (Max)	36 dB(A)
	MTTF	> 50,000 hours
	Bearing	Loop dynamic bearing
	Connector	4-Pin PWM
	Rated Voltage	12 VDC
	Rated Current	0.15 A
	Safety Current	0.25 A
	Power Consumption	1.8 W



MASTERLIQUID ATMOS II STEALTH SPECIFICATIONS

Model Name	MasterLiquid Atmos II Stealth 240	
Model Number	MLX-D24M-A24DK-R1	
Fan	Dimensions	120 x 120 x 25 mm (4.7 x 4.7 x 1.0 inch)
	Profiles	NON LED
	Quantity (pcs)	2 PCS
	Speed	0 ~ 2400 RPM ± 10%
	Air Flow (Max)	127.8 m³/h (75.2 CFM)
	Air Pressure (Max)	3.63 mmH₂O
	Noise Level (Max)	30 dB(A)
	MTTF	> 200,000 hours
	Bearing	Loop dynamic bearing
	Connector	4-Pin PWM
	Rated Voltage	12 VDC
	Rated Current	0.18 A
	Safety Current	0.35 A
	Power Consumption	2.16 W
Warranty	6 years	

Model Name	MasterLiquid Atmos II Stealth 360	
Model Number	MLX-D36M-A24DK-R1	
Fan	Dimensions	120 x 120 x 25 mm (4.7 x 4.7 x 1.0 inch)
	Profiles	NON LED
	Quantity (pcs)	3 PCS
	Speed	0 ~ 2400 RPM ± 10%
	Air Flow (Max)	127.8 m³/h (75.2 CFM)
	Air Pressure (Max)	3.63 mmH₂O
	Noise Level (Max)	30 dB(A)
	MTTF	> 200,000 hours
	Bearing	Loop dynamic bearing
	Connector	4-Pin PWM
	Rated Voltage	12 VDC
	Rated Current	0.18 A
	Safety Current	0.35 A
	Power Consumption	2.16 W
Warranty	6 years	

SHIPPING DETAILS

MasterLiquid Atmos II Stealth Series		240	360
EAN Code		MLX-D24M-A24PK-R1: 4719512155134	MLX-D36M-A24PK-R1:4719512155141
UPC Code		MLX-D24M-A24PK-R1: 884102127458	MLX-D36M-A24PK-R1:884102127465
Net Weight		1.39kg	1.68 kg
Gross Weight		1.97 kg	2.54 kg
Packaging dimension (L x W x H)		292 x 211 x 136 mm	410 x 211 x 136 mm
Carton Dimension (L x W x H)		440 x 320 x 310 mm	442 x 440 x 310 mm
Unit / Pallet		144 / 168	96 / 112
Unit Per Box		4	4
Container 20 feet	With Pallet	1728	1152
	Carton / Pallet	36	24
	Without Pallet	N/A	N/A
Container 40 feet	With Pallet	3456	2304
	Carton / Pallet	36	24
	Without Pallet	N/A	N/A
Container 40 HQ	With Pallet	4032	2688
	Carton / Pallet	42	28
	Without Pallet	N/A	N/A