




ALSEYE X360 – 360mm AiO water cooling

The X360 AiO water cooling of the X series from ALSEYE impresses with its compact design and, thanks to the cooling plate made of copper and the radiator made of pure aluminum, ensures that the generated heat is reliably removed. The three 120mm X12 fans reliably transport the heat away at up to 1600 rpm and also shine in rich RGB colors.

The lighting and fan speed are controlled centrally via the enclosed control unit, to which up to five additional X12 fans, which are available separately, can be connected. The RGB effects can be managed either via the RF wireless remote control or via the 5V 3pin RGB header.

The pump with high-quality ceramic bearing and integrated RGB LEDs as well as the high-quality sleeved, swiveling FEP tubes with a length of 350 mm ensure safe, reliable and long-lasting operation.

- ✓ AiO water cooling with a compact design
- ✓ High quality materials made of copper and aluminum
- ✓ Three powerful 120mm X12 fans with RGB lighting
- ✓ TDP up to 350W

Specifications

CPU sockets	Intel® Socket LGA2011, 2066 Square ILM Intel® Socket LGA775, 1150, 1151, 1155, 1156, 1200, 1366 AMD® Socket AM2, AM2+, AM3, AM3+, FM1, FM2, AM4
Fan dimensions (H/W/D)	120x120x30mm
Rated voltage	12V
Fan speed	1600U/min
Air flow per fan	95.65m³/h
Air pressure per fan	1.97mmH ₂ O
Noise level	35.6dbA
Fan connector	4pin PWM
Tube length	350mm
Cooling fluid	Ecofriendly liquid with anti-corrosion protection
Net dimensions (H/W/D)	Water block: 62/62/90mm Radiator: 27/393/120mm
Package dimensions (H/W/D)	438/210/145mm
Weight (net)	1.53kgs
Weight (gross)	1.895kgs
Packing units (VE/VPE)	1/6
Warranty	24 Months
Article number	88885515
EAN-Code	4897059872735
Scope of delivery	Mounting kit for Intel® Socket LGA775, 1150, 1151, 1155, 1156, 1200, 1366, 2011, 2066 Square ILM Mounting kit for AMD® Socket AM2, AM2+, AM3, AM3+, FM1, FM2, AM4 Backplate-mounting kit Control unit for X12 fan (magnetically attachment in the case, up to 8 fans connectable in total) RF wireless remote control Power cord for control unit (Connection over S-ATA power connector) Combo cable for 5V 3pin RGB header and PWM Thermal compound Manual (English)
Features	Cooling plate with copper base Pump with high quality ceramic bearing and RGB LEDs Space-saving radiator made of pure aluminum 3x 120mm X12 fans with each 26 RGB LEDs RGB LEDs controllable via remote control or 5V 3pin RGB 3pin RGB header connection for 5V RGB mainboard control High quality sleeved, swiveling FEP tubes Supports CPUs with a max. TDP of 350W