

C2-Pro-IP-Camera-Specifications

	Model	C2 Pro	
Hardware Features	Image Sensor	1/2.7" CMOS Sensor	
	Display Resolution	2560 x 1920 (5.0 Megapixels)	
	Lens	f=2.8-8mm Autofocus, F=1.6, with IR Cut	
	Angle of View	Horizontal: 48° ~ 92° Vertical: 37° ~ 70°	
	Pan/Tilt Angle	Horizontal: 355° Vertical: 105°	
	Minimum Illumination	0 Lux (with IR Illuminator)	
	IR Distance	12 Meters (40ft) (LED: 8pcs/14mil/850nm)	
	Dimension	103 x 95 x 117mm	
	Weight	300g	
	Power Input	5.0V/2A, <6W	
	Interface		One 10M/100Mbps RJ45 Power Interface Micro SD Card Slot Built-in Microphone and Speaker Reset Button
		Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, UPNP, RTSP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
Image Compression		H.264	
Software Features	Maximal Frame Rate	PAL/NTSC: 25fps	
	Code Rate	1024Kbps ~ 8192Kbps	
	Audio	Two-Way Audio	
	Maximal User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)	
	Browser Supported	IE, Edge, Chrome, Firefox, Safari	
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android	
	Record Mode	Motion Record/Schedule Record (Default: Motion Record)	
Wireless Features	Wireless Standard	IEEE 802.11a/b/g/n	
	Operating Frequency	2.4GHz/5GHz	
	Wireless Security	WPA-PSK/WPA2-PSK	
Other Parameters	Temperature	Operating Temperature: -10°C~+55°C Storage Temperature: -40°C~70°C	
		Operating Humidity: 20% ~ 85% Storage Humidity: 10% ~ 90%	
	Humidity		
	Waterproof	No	