










IB-DK4034a-CPD
6-in-1 USB Type-C® Notebook Docking Station





1x



1x




Legacy USB standards	Current USB standards	Data transfer rate
USB 3.0 = USB 3.1 (Gen 1)	= USB 3.2 Gen 1	= 5 Gbit/s
USB 3.1 = USB 3.1 (Gen 2)	= USB 3.2 Gen 2	= 10 Gbit/s
USB 3.2 (Gen 2x2)	= USB 3.2 Gen 2x2	= 20 Gbit/s
	= USB4® Gen 2x1	= 10 Gbit/s
	= USB4® Gen 2x2	= 20 Gbit/s
	= USB4® Gen 3x2	= 40 Gbit/s




www.icybox.de



1



2



Nos produits et emballages se recyclent, ne
les jetez pas! Trouvez où les déposer sur le site
www.quefairedemesdechets.fr

© Copyright 2024 by RaidSonic Technology GmbH. All Rights Reserved.
The information contained in this manual is believed to be accurate and reliable. Raid-
Sonic Technology GmbH assumes no responsibility for any errors contained in this
manual. RaidSonic Technology GmbH reserves the right to make changes in the spe-
cifications and/or design of the above-mentioned product without prior notice. The
diagrams contained in this manual may also not fully represent the product that you
are using and are there for illustration purposes only. RaidSonic Technology GmbH
assumes no responsibility for any differences between the product mentioned in this
manual and the product you may have. Apple and macOS are registered trademarks
of Apple Computer Inc. Microsoft, Windows and the Windows logo are registered
trademarks of Microsoft Corporation. The terms HDMI, HDMI High-Definition Multi-
media Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered
trademarks of HDMI Licensing Administrator, Inc.