



SPEZIFIKATIONEN

FRAME	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBEN	Black
RAHMEN	ALUXX-Grade Aluminum, 12x142mm thru-axle, disc, flip chip dropout
GABEL	Advanced-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	cork tape with gel
VORBAU	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SATTELSTÜTZE	Giant D-Fuse, alloy, 14mm offset
SATTEL	Giant Approach
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	Shimano GRX RX-600, 2x11
UMWERFER	Shimano GRX RX-810
SCHALTWERK	Shimano GRX RX-810
BREMSEN	Shimano GRX RX-400 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BREMSHEBEL	Shimano GRX RX-600 hydraulic
KASSETTE	Shimano 105, 11x34
KETTE	KMC X11 with Missing Link
KURBELSATZ	Praxis Alba 2D, 32/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
TRETLAGER	Praxis M24, press fit
LAUFRÄDER	
FELGEN	Giant S-X2 Disc wheelset
NABEN	Giant S-X2 Disc wheelset
SPEICHEN	Giant S-X2 Disc wheelset
REIFEN	Giant CrossCut AT 1, 700x38c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 42mm max tire size in "short" flip chip position

ERFAHREN SIE MEHR...

- Rahmen: ALUXX-Grade Aluminum, 12x142mm thru-axle, disc, flip chip dropout
- Gabel: Advanced-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
- Schalthebel: Shimano GRX RX-600, 2x11
- Kurbelsatz: Praxis Alba 2D, 32/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
- Farben: Black

Preis: € 1.799

GEOMETRIEDATEN

FRAME	XS		S		M		ML		L		XL
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT
Sitzrohrlänge (mm)	430	450	470	490	510	530					
Sitzrohrwinkel	74,0°	73,5°	73,5°	73,0°	73,0°	73,0°					
Oberrohrlänge (mm)	540	550	560	575	585	600					
Steuerrohrlänge (mm)	125	135	150	165	180	195					
Steuerrohrwinkel	70,0°	71,0°	71,5°	72,0°	72,0°	72,0°					
Gabel (mm)	50	50	50	50	50	50					
Spur (mm)	78 82	72 75	68 72	65 68	65 68	65					
Radstand (mm)	1029 1039	1025 1035	1030 1040	1035 1045	1045 1055	1060					
Kettenstrebenlänge (mm)	430 440	430 440	430 440	430 440	430 440	430					
Tretlager (mm)	80 81	80 81	80 81	80 81	80 81	80					
Stapel (mm)	556	570	586	602	616	630					
Reichweite (mm)	381	381	387	391	397	407					
Überstandshöhe (mm)	717 724	734 741	752 759	769 776	786 793	801					
Lenkerbreite (mm)	420	420	440	440	460	460					
Vorbaulänge (mm)	70	80	90	100	100	110					
Kurbellänge (mm)	170	170	172,5	172,5	175	175					
Radgröße	700x 42C 50C 700x 42C 50C 700x 42C 50C 700x 42C 50C 700x 42C 50C 700x 42C 50C 700x 42C 50C 700x 42C 50C 700x 42C 50C 700x 42C 50C 700x 42C										

Preis- und Farbänderungen vorbehalten. Aufgrund der aktuell durch das Corona-Virus verursachten Probleme in den Lieferketten sämtlicher Zulieferer kann das Bike, entgegen der hier kommunizierten Spezifikation, mit abweichenden Komponenten ausgeliefert werden.