

Hammer Driver Drill LXT® - Olive

DHP482SFO

18V, 62 Nm, 0 – 1 900 min⁻¹

Powerful general-use combi drill with hammer action for professionals



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 600 / 1900 min ⁻¹
Max. fastening torque Hard/Soft	62 / 36 Nm
Torque setting	21
Impacts per Minute (IPM)	0 - 9000 / 28 500 min ⁻¹
Max. Drilling Diameter in Wood	38 mm
Max. Drilling Diameter in Masonry	13 mm
Max. Drilling Diameter in Concrete	13 mm
Max. Drilling Diameter in Steel	13 mm
Driving Shank	1/2"-20UNF "
Drill Chuck Capacity	1,5 - 13 mm
Sound Power Level (L _{WA})	93 dB(A)
Sound Pressure Level (L _{pA})	82 dB(A)

User benefits

- 4-pole motor in compact design without torque loss at low power consumption
- Highly efficient and compact machine for professional use
- Optimal handle design
- Battery protection system automatically shuts off power when the battery level is low
- LED light illuminates the work site

EAN 0088381770712

Link to product - www.makita.uk.com



Related products

Standard MA

DC18SD
Battery Charger LXT®



BL1830B
Battery LXT® 3,0 Ah

