

PRODUCT-DETAILS

DS202 A-K16/0,03

DS202 A-K16/0,03 - RCBo



General Information

| | |
|-----------------------|--|
| Extended Product Type | DS202 A-K16/0,03 |
| Product ID | 2CSR252101R1167 |
| EAN | 8012542930501 |
| Catalog Description | DS202 A-K16/0,03 - RCBo |
| Long Description | The RCBOs DS200 series has the function to protect against overload and short-circuit currents; protection against the effects of sinusoidal alternating earth fault currents; protection against indirect contacts and additional protection against direct contacts. |

Technical

| | |
|---------------------------|----------------------------------|
| Standards | IEC/EN 60947-2 IEC/EN 61009-1 |
| Operating Characteristic | Instantaneous |
| Type of Residual Current | A type |
| Number of Poles | 2 |
| Number of Protected Poles | 2 |
| Rated Current (I_n) | 16 A |
| Rated Voltage (U_r) | 230 V AC |
| Rated Frequency (f) | 50/60 Hz |
| Rated Short-Circuit | 6 kA |

Capacity (I_{cn})

| | |
|---|--|
| Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}) | (400 V AC) 10 kA |
| Tripping Characteristic | K |
| Electrical Endurance | 10000 cycle |
| Connecting Capacity | Busbar 10 mm ² Rigid 25 ...25 mm ² Flexible 25 ...25 mm ² |
| Power Supply Connection | Arbitrary |
| Position of Neutral Terminals | Right |
| Power Loss | 4.9 W |

Environmental

| | |
|-------------------------|--|
| Ambient Air Temperature | Operation -25 ... +55 °C Storage -40 ... +70 °C |
|-------------------------|--|

Technical UL/CSA

| | |
|-------------------------------------|-------|
| Short-Circuit Current Rating (SCCR) | 30 mA |
|-------------------------------------|-------|

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 70 mm |
| Product Net Height | 0.093 m |
| Product Net Depth / Length | 69 mm |
| Product Net Weight | 0.440 kg |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 0.105 m |
| Package Level 1 Height | 0.08 m |
| Package Level 1 Depth / Length | 0.08 m |
| Package Level 1 Gross Weight | 0.48 kg |
| Package Level 1 EAN | 8012542930501 |

Ordering

| | |
|------------------------|----------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85389099 |

Certificates and Declarations (Document Number)

| | |
|-----------------------------------|-----------------|
| Declaration of Conformity - CE | 9AKK106713A5607 |
| Environmental Information | Refer to RoHS |
| Instructions and Manuals | 9AKK107045A1451 |
| RoHS Information | 2CSC423002K2701 |

Popular Downloads

| | |
|--------------------------------------|-----------------|
| Data Sheet, Technical Information | 9AKK107046A0424 |
| Instructions and Manuals | 9AKK107045A1451 |

Classifications

| | |
|----------------------------|---|
| Object Classification Code | Q |
| ETIM 4 | EC002281 - Distributor assembly with combination RCCB/MCB |
| ETIM 5 | EC002281 - Distributor assembly with combination RCCB/MCB |
| ETIM 6 | EC002281 - Distributor assembly with combination RCCB/MCB |
| ETIM 7 | EC002281 - Distributor assembly with combination RCCB/MCB |

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Circuit Breakers with Overcurrent Protection RCBO

