



DATASHEET

Network Cabinet PRO 18U, 600x600 mm, RAL7035



General data

19" network cabinet according to DIN41494

Steel sheet housing with screwed frame, completely pre-assembled, self-ventilated, dismantlable

Inside front and rear 4 x 19" profiles (2 front, 2 rear-sided), galvanised, step-less depth-adjustable

Contrariwise numbering of rack units at the 19" profiles

Front door with window of certified safety glass (thickness 5 mm)

Front door with 3-point turning handle (up to 24U 1-point), lockable, incl. profile half-cylinder acc. to DIN18252 / EN 1303

Profile half-cylinder exchangeable by customer (30/10 mm)

Rear door steel, 1-part, shortened, with 2 x latch locking (lock equal to door lock), 3U panel for cable entry below (690 x 67 mm)

Door stop for front and rear door possible left- or right-sided

Detachable side walls with 2 x latch locking (lock equal to the door lock)

Cabinets stackable side-by-side with and without removal of the side walls, baying set (Art.-No. PRO-ANR0X)

Roof and bottom with 4/6 pre-punched openings for cable entry (450 x 90 mm), for 600 mm cabinet width cable entry only rear

Roof prepared for accommodation of 2-fan or 4-fan units, bottom with pre-punched opening for filter or cable entry modules

Internal earthing of all cabinet sections

Pre-assembled earthing bar rear-sided in the middle of the cabinet (ports: 2 x M5 + 2 x 8 mm)

Max. load 1000 kg (depths 600 / 800 mm) resp. 1360 kg (depths 1000 / 1200 mm for >24U)

This datasheet was created automatically on 11-09-2025 . Technical changes reserved.



DATASHEET

Network Cabinet PRO 18U, 600x600 mm, RAL7035

Paint finish RAL7035, light grey

Protection degree IP20

Included accessories: 1 x brush, 1 x set of captive nuts (PU 20 pcs.), earthing bar and earthing cables, 4 x levelling feet M12, 2 x key

Delivery in transport packaging on disposable pallet

Technical properties

Cabinet Series	
Degree of protection	
Demountable	
Material	
Model	
Modular spacing	
Mounting level	
Number of cartons	
Surface finishing	
Type of back door	
Type of front door	
Type of profile rail	
Type of ventilation	
With backside door	
With earthing	
With front door	
With roof plate	
With sidewall	
With socket	

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Number of height units	Width	Höhe	RAL-Nummer	Anzahl der Türen
PRO-4266GR.G1SV	Network Cabinet PRO 42U, 600x600 mm, RAL7035	grey	600 mm	42 U	600 mm	1963 mm	7035	2
PRO-4266TS.G1SV	Network Cabinet PRO 42U, 600x600 mm, RAL9005	schwarz	600 mm	42 U	600 mm	1963 mm	9005	2
PRO-3366GR.G1SV	Network Cabinet PRO 33U, 600x600 mm, RAL7035	grey	600 mm	33 HE	600 mm	1563 mm	7035	2
PRO-2466GR.G1SV	Network Cabinet PRO 24U, 600x600 mm, RAL7035	grey	600 mm	24 HE	600 mm	1163 mm	7035	2

This datasheet was created automatically on 11-09-2025 . Technical changes reserved.



DATASHEET

Network Cabinet PRO 18U, 600x600 mm, RAL7035

PRO-2466TS.G1SV	Network Cabinet PRO 24U, 600x600 mm RAL9005	black	600 mm	24 U	600 mm	1163 mm	9005	2
PRO-1866GR.G1SV	Network Cabinet PRO 18U, 600x600 mm, RAL7035	grey	600 mm	18 HE	600 mm	896 mm	7035	2

This datasheet was created automatically on 11-09-2025 . Technical changes reserved.

